

## **VEGAPOINT 24**

Version, available since	Description	Device Rev.
1.2.0, 06/2023	<ul> <li>Error corrections:</li> <li>Wrong switching point values were displayed in the app/DTM during user-defined adjustment.</li> </ul>	2049
1.1.0, 01/2023	<ul> <li>Error corrections: <ul> <li>Hysteresis of the switching outputs did not work if the switch-on or switch-off delay was exactly 0 seconds</li> <li>Software update did not work with simultaneous IO-Link communication</li> <li>With datastorage IO-Link, the switching points were not written into the sensor</li> <li>The Upload Flag was not set correctly with IO-Link</li> <li>During the start phase, snesors without Bluetooth are flashing blue</li> <li>Default values are stored for customised live adjustment</li> </ul> </li> </ul>	2049
1.0.0, 04/2021	First version New functions: Measurement function: - For conductive and capacitive probe Outputs: - Switching outputs Instrument software, in general: - Device status according to NE107 - Pointer - IO-Link 1.1 communication - Adjustment via Bluetooth 5.0	2049

## Overview of the software versions



## Legend:

Name	Description	
Version	<ul> <li>xx.yy.zz</li> <li>xx: Compatibility version. Will be increased when the compatibility to the previous version is no longer given. Value range 0 99.</li> <li>yy: Function extension version. Will be increased when new functions or function changes were carried out on the previous version. Also errors can have been corrected with a function change. Value range 0 99.</li> <li>zz: Error correction version. Will be increased when only errors were corrected on the previous version. Value range 0 99.</li> </ul>	
available since	Month/Year	
Device Rev.	Version number of the instrument defined by Fieldbus. Consecutive integral number Will be increased if in the "Application Layer" modifications were carried out, e.g. new commands, modifications in the data structure in a command.	