



#### Reliable

High measurement reliability, even in extremely dusty environments

#### Cost effective

Maintenance-free operation

#### User friendly


Simple to set up

## Filling silo for colour pigment

### Level measurement and point level detection in colour pigment packing

In the last production step, the finished pigment powders are pneumatically conveyed into packing silos. The conveying system generates very high dust levels and air movement inside the silos. To control the filling process, the levels in the silos need continuous monitoring. A high level detection switch is used for safety shutdown in case of overfilling. The pigment powder is then filled into sacks via the bottom outlet.

[More details](#)



#### VEGAFLEX 82

Continuous level measurement with guided radar in filling silo

- Accurate measurement despite extremely dusty environment
- Reliable level measurement, even in media with low dielectric constant
- Simple and fast setup with display and adjustment module

[Show Product](#)



#### VEGAWAVE 63

Vibrating level switch for protection against overfilling

- Simple setup without calibration
- Reliable detection despite changing density of the medium
- Dependable function thanks to product-independent switching point

[Show Product](#)

PRO

PRO

## VEGAFLEX 82

[Show Product](#)



## VEGAWAVE 63

[Show Product](#)


**Measuring range - Distance**

75 m

**Process temperature**

-40 ... 200 °C

**Process pressure**

-1 ... 40 bar

**Accuracy**

± 2 mm

**Version**

Basic version for exchangeable cable ø 4, ø 6 PA coat.  
 Basic version for exchangeable cable ø 6, ø 11 PA coat.,  
 rod ø 16  
 Exchangeable rod ø 16 mm  
 Exchangeable cable ø 2 mm with gravity weight  
 Exchangeable cable ø 6 mm with gravity weight  
 Exchangeable, PA-coated steel cable ø 6 mm with gravity  
 weight  
 Exchangeable, PA-coated steel cable ø 11 mm with  
 gravity weight

**Materials, wetted parts**

316L  
 Alloy C22 (2.4602)  
 PA

**Threaded connection**

≥ G¾, ≥ ¾ NPT

**Flange connection**

≥ DN25, ≥ 1"

**Seal material**

EPDM  
 FKM  
 FFKM

**Housing material**

Plastic  
 Aluminium  
 Stainless steel (precision casting)  
 Stainless steel (electropolished)

**Measuring range - Distance**

-

**Process temperature**

-50 ... 250 °C

**Process pressure**

-1 ... 25 bar

**Version**

Detection of solids in water  
 with tube extension  
 with temperature adapter

**Materials, wetted parts**

316L

**Threaded connection**

≥ G1½, ≥ 1½ NPT

**Flange connection**

≥ DN50, ≥ 2"

**Hygienic fittings**

Clamp ≥ 2", DN50 - DIN32676, ISO2852

**Seal material**

no media contact

**Housing material**

Plastic  
 Aluminium  
 Stainless steel (precision casting)  
 Stainless steel (electropolished)