



#### Reliable

Reliable measurement despite high temperatures

#### Cost effective

Optimal stocks enable continuous production

#### User friendly

Maintenance-free operation

## Clinker silo

### Level measurement and point level detection in clinker silos

After the raw meal is burned, the emerging clinker of varying consistency is stored for further processing. The silos are filled and emptied through different openings. Continuous operation of the subsequent production processes is ensured by level measurement and point level detection.

[More details](#)



#### VEGAPULS 6X

Level measurement with radar in clinker silos

- Exact measurement right to the bottom of the discharge funnel thanks to small beam angle
- High measurement certainty, unaffected by dust and temperature changes
- Maintenance-free through non-contact measurement

[Show Product](#)



#### VEGACAP 65

Capacitive point level detection in clinker silos

- Robust construction ensures a long service life
- Reliable measurement, unaffected by buildup
- Cut to length cable probes allow high flexibility

[Show Product](#)

PRO

PRO

**VEGAPULS 6X**[Show Product](#)**Measuring range - Distance**

120 m

**Process temperature**

-196 ... 450 °C

**Process pressure**

-1 ... 160 bar

**Accuracy**

± 1 mm

**Frequency**

6 GHz

26 GHz

80 GHz

**Beam angle**

≥ 3°

**Materials, wetted parts**

PTFE

PVDF

316L

PP

PEEK

**Threaded connection**

≥ G¾, ≥ ¾ NPT

**Flange connection**

≥ DN20, ≥ ¾"

**Hygienic fittings**

Clamp ≥ 1½" - DIN32676, ISO2852

Slotted nut ≥ 2", DN50 - DIN 11851

Varivent ≥ DN25

hygienic fitting with tension flange DN32

hygienic fitting F40 with compression nut

Hygienic screw connections ≥ DN50 tube ø53 -

DIN11864-1-A

Hygienic flange connection ≥ DN50 DIN11864-2

Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-

3-A

DRD connection ø 65 mm

SMS 1145 DN51

**VEGACAP 65**[Show Product](#)**Measuring range - Distance**

-

**Process temperature**

-50 ... 200 °C

**Process pressure**

-1 ... 64 bar

**Version**

Cable ø 6 mm with screening tube without weight

Cable ø 6 mm with screening tube and gravity weight

Cable ø 6 mm with gravity weight

Cable ø 8 mm with abrasion protection without weight

Cable ø 8 mm with abrasion protection and gravity weight

Cable ø 8 mm with gravity weight

PA cable ø 12 mm with screening tube and gravity weight

**Materials, wetted parts**

PTFE

316L

PA

PEEK

Steel

**Threaded connection**

≥ G1, ≥ 1 NPT

**Flange connection**

≥ DN50, ≥ 2"

**Housing material**

Plastic

Aluminium

Stainless steel (precision casting)

Stainless steel (electropolished)

**Protection rating**

IP66/IP68 (0,2 bar)

IP66/IP67

IP66/IP68 (1 bar)

**Output**

Relay (DPDT)

Contactless electronic switch

Transistor (NPN/PNP)

Two-wire