

Reliable


Highly overload-resistant measuring systems

Cost effective

Accurate level measurement for optimal utilization of the container volumes

User friendly

Easy instrument selection: one sensor version fits all tank sizes



Expansion tank in a thermal solar plant

Level and pressure measurement of heat transfer fluid(HTF) in expansion tanks

The solar heat captured in the mirror system of a thermal solar plant is transported via a heat transfer fluid (HTF) to the steam generator at the central turbine. The HTF normally has a temperature between 300 °C and 400 °C. There are different containers for the fluid across the plant and the varying temperatures cause volume changes to the HTF that need to be accurately measured to operate the plant safely and profitably.

More details



VEGAPULS 6X

Non-contact level measurement with radar in the expansion vessel for heat transfer fluid

- Reliable function, even at high temperatures
- High-resistance materials guarantee long service life
- Wear-free operation ensured through non-contact measuring method

Show Product



VEGABAR 81

Pressure measurement in the thermal solar plant pipeline systems

- Highly resistant to overloading due to pressure surges
- Long service life thanks to seal-free measuring cells
- Wear and maintenance-free due to high-resistance diaphragm materials

Show Product



VEGAPULS 6X Show Product



Measuring range - Distance

120 m

Process temperature

-196 ... 450 °C

Process pressure

-1 ... 160 bar

Accuracy

± 1 mm

Frequency

6 GHz 26 GHz

80 GHz

Beam angle

≥ 3°

Materials, wetted parts

PTFE

PVDF

316L PP

PEEK

Threaded connection

 \geq G³/₄, \geq ³/₄ NPT

Flange connection

≥ DN20, ≥ ¾"

Hygenic fittings

Clamp $\geq 1\frac{1}{2}$ " - DIN32676, ISO2852

Slotted nut ≥ 2", DN50 - DIN 11851

Varivent ≥ DN25

hygienic fitting with tension flange DN32

hygienic fitting F40 with compression nut

Hygienic screw connections \geq DN50 tube ø53 -

DIN11864-1-A

Hygienice flange connection ≥ DN50 DIN11864-2

Hygienic clamp connection \geq DN50 pipe Ø53 - DIN11864-

3-A

DRD connection ø 65 mm

SMS 1145 DN51

VEGABAR 81

Show Product



Measuring range - Distance

-

Measuring range - Pressure

-1 ... 1000 bar

Process temperature

-90 ... 400 °C

Process pressure

-1 ... 1000 bar

Accuracy

0.2 % 0.1 %

Materials, wetted parts

Alloy C22 (2.4602)

Alloy 400 (2.4360)

Tantalum

Alloy C276 (2.4819)

Duplex (1.4462)

Titanium Grade 2 (3.7035)

1.4435

316/316L

Titanium Grade 7 (3.7235)

Threaded connection

≥ G½, ≥ ½ NPT

Flange connection

≥ DN25, ≥ 1"

Hygenic fittings

Clamp ≥ 1" - DIN32676, ISO2852

Slotted nut $\geq 1\frac{1}{2}$ ", \geq DN40 - DIN 11851

hygienic fitting with tension flange $\ensuremath{\mathsf{DN32}}$

hygienic fitting F40 with compression nut

Hygienice flange connection ≥ DN50 DIN11864-2

Hygienic fittings ≥ DN40 - DIN11864-1-A

Seal material

no media contact

