



Reliable

Approved materials acc. to FDA and EC 1935/2004

Cost effective

Continuous coating is ensured thanks to maintenance-free operation

User friendly


Simple mounting

Drum coater storage tank

Level measurement and point level detection in the storage tank of a drum coater

In the pharmaceutical industry, tablets are coated with colouring agents or active ingredients in a drum coater. This coating in the form of a liquid suspension, contains colouring or solids and is stored in a storage tank next to the drum. It is sprayed into the drum via nozzles for even distribution on the surface of the tablets. Reliable level measurement in the storage tank is required to ensure that there is always enough of the liquid suspension for tablet coating. Overflow and dry run protection is provided by a reliable level switch.

[More details](#)



VEGAPOINT 21

Capacitive level switch as overflow and dry run protection in a supply tank

- Simple operation, including optical switching display
- Reliable switching point, non-sensitive to buildup
- Compact design ideally suited for tight spaces

[Show Product](#)



VEGAPULS 6X

Non-contact level measurement with radar in a storage tank

- Reliable and accurate measurement even in small tanks
- Approved materials according to FDA and EC 1935/2004 ensure hygienic storage of the suspension
- Direct measured value display on the sensor and via Bluetooth for easy visualization of the container contents

[Show Product](#)

BASIC

PRO

VEGAPOINT 21

[Show Product](#)

VEGAPULS 6X

[Show Product](#)

Measuring range - Distance -	Measuring range - Distance 120 m
Process temperature -40 ... 115 °C	Process temperature -196 ... 450 °C
Process pressure -1 ... 64 bar	Process pressure -1 ... 160 bar
Materials, wetted parts 316L PEEK	Accuracy ± 1 mm
Threaded connection ≥ G½, ≥ ½ NPT	Frequency 6 GHz 26 GHz 80 GHz
Hygienic fittings Clamp ≥ 2", DN50 - DIN32676, ISO2852 Clamp ≥ 1" - DIN32676, ISO2852 Clamp ≥ 1½" - DIN32676, ISO2852 Slotted nut ≥ 1½", ≥ DN40 - DIN 11851 Slotted nut ≥ DN25 - DIN 11851 Slotted nut ≥ DN32 - DIN 11851	Beam angle ≥ 3°
Seal material EPDM FKM	Materials, wetted parts PTFE PVDF 316L PP PEEK
Protection rating IP66/IP67 IP69	Threaded connection ≥ G¾, ≥ ¾ NPT
Output Transistor (NPN/PNP) IO-Link	Flange connection ≥ DN20, ≥ ¾"
Ambient temperature -40 ... 70 °C	Hygienic fittings Clamp ≥ 1½" - DIN32676, ISO2852 Slotted nut ≥ 2", DN50 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 hygienic fitting F40 with compression nut Hygienic screw connections ≥ DN50 tube ø53 - DIN11864-1-A Hygienic flange connection ≥ DN50 DIN11864-2 Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864- 3-A DRD connection ø 65 mm SMS 1145 DN51