



#### Reliable

Reliable measurement, unaffected by surface, foam and condensation

#### Cost effective

Maintenance-free operation

#### User friendly

Simple installation

## Sugar dissolver vessel

### Level measurement in the sugar dissolver vessel

In beet sugar refining the raw sugar is heated and dissolved in water into liquor. There are typically several interconnected agitated vessels in this process, each one with a weir allowing the liquor to flow from vessel to vessel. During the dissolving process, sugar byproducts from the downstream refining process are reintroduced to enable sugars to be recovered. To ensure a continuous process, a reliable level measurement is required.

[More details](#)



### VEGAPULS 6X

Radar level measurement in the sugar dissolver vessel

- Reliable measurement in small vessels, independent of condensation and foam
- Hygienic process fittings allow aseptic operation
- Easy installation thanks to small process fittings

[Show Product](#)

**VEGAPULS 6X**[Show Product](#)**Measuring range - Distance**

120 m

**Process temperature**

-196 ... 450 °C

**Process pressure**

-1 ... 160 bar

**Accuracy**

± 1 mm

**Frequency**

6 GHz

26 GHz

80 GHz

**Beam angle**

≥ 3°

**Materials, wetted parts**

PTFE

PVDF

316L

PP

PEEK

**Threaded connection**

≥ G¾, ≥ ¾ NPT

**Flange connection**

≥ DN20, ≥ ¾"

**Hygienic fittings**

Clamp ≥ 1½" - DIN32676, ISO2852

Slotted nut ≥ 2", DN50 - DIN 11851

Varivent ≥ DN25

hygienic fitting with tension flange DN32

hygienic fitting F40 with compression nut

Hygienic screw connections ≥ DN50 tube ø53 -

DIN11864-1-A

Hygienic flange connection ≥ DN50 DIN11864-2

Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-

3-A

DRD connection ø 65 mm

SMS 1145 DN51