



Reliable

Reliable measurement, independent of media properties and container geometry

Cost effective

Maintenance-free operation

User friendly

Universally applicable for almost all bulk solids

Silos for bulk solids

Level measurement and point level detection in silos

In the chemical industry, many different kinds of bulk solids are produced or used as raw materials. To ensure reliable measurement of silo contents, many factors must be considered: different bulk densities, abrasive properties, dust generation and the requirements of explosion protection. Implementation of the most suitable level sensors ensures optimal production planning and reliable logistics for the finished products.

[More details](#)



VEGAPULS 6X

Non-contact radar level measurement in bulk solids silos

- Reliable measurement even with large amounts of dust and filling noise
- Suitable even for high, narrow silos or segmented containers, thanks to good signal focusing
- Can be used in media of differing consistency and in different measuring ranges
- Simple installation and calibration, even on filled silos

[Show Product](#)



VEGAVIB 63

Point level detection with vibrating level switches in bulk solids silos

- Universally applicable for all granulated bulk solids
- Wear and maintenance-free measurement
- Simple, adjustment-free setup and commissioning

[Show Product](#)

PRO

VEGAPULS 6X

[Show Product](#)



Measuring range - Distance
120 m

Process temperature
-196 ... 450 °C

Process pressure
-1 ... 160 bar

Accuracy
± 1 mm

Frequency
6 GHz
26 GHz
80 GHz

Beam angle
≥ 3°

Materials, wetted parts
PTFE
PVDF
316L
PP
PEEK

Threaded connection
≥ G¾, ≥ ¾ NPT

Flange connection
≥ DN20, ≥ ¾"

Hygienic fittings
Clamp ≥ 1½" - DIN32676, ISO2852
Slotted nut ≥ 2", DN50 - DIN 11851
Varivent ≥ DN25
hygienic fitting with tension flange DN32
hygienic fitting F40 with compression nut
Hygienic screw connections ≥ DN50 tube ø53 -
DIN11864-1-A
Hygienic flange connection ≥ DN50 DIN11864-2
Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A
DRD connection ø 65 mm
SMS 1145 DN51

PRO

VEGAVIB 63

[Show Product](#)



Process temperature
-50 ... 250 °C

Process pressure
-1 ... 16 bar

Version
Detection of solids in water
with tube extension

Materials, wetted parts
316L

Threaded connection
≥ G1, ≥ 1 NPT

Flange connection
≥ DN 32, ≥ 1½"

Hygienic fittings
Slotted nut ≥ 1½", ≥ DN40 - DIN 11851
Slotted nut ≥ 2", DN50 - DIN 11851
Varivent ≥ DN32
hygienic fitting with tension flange DN32
hygienic fitting F40 with compression nut
Hygienic screw connections ≥ DN50 tube ø53 -
DIN11864-1-A
Clamp ≥ 3½", DN80 - DIN32676, ISO2852
Slotted nut ≥ 3", DN65 - DIN 11851
Hyg. collar clamp adapter DN40PN40 DIN11864-3-A

Seal material
no media contact

Housing material
Plastic
Aluminium
Stainless steel (precision casting)
Stainless steel (electropolished)

Protection rating
IP66/IP68 (0,2 bar)
IP66/IP67
IP66/IP68 (1 bar)