



### Reliable

Better, consistent product quality, because of precise monitoring

### Cost effective

Simple setup and commissioning, completely maintenance free

### User friendly

Universal, media-independent measurement technology

## Silage tank

### Level measurement and point level detection in the storage tank for fish waste

Fish waste and scraps are the valuable raw material for fish silage, which in turn is a protein-rich raw material for the production of fish meal and dry fish feed. The acids used during production enable controlled growth of bacteria. The levels in the storage tanks must be carefully and reliably monitored. The visualisation of current process and storage status is handled by VEGA Inventory System.

#### More details



### VEGAPULS 6X

Non-contact level measurement with radar in the silage tank

- Maintenance-free operation thanks to non-contact measuring principle
- Simple installation and setup
- Reliable measurement unaffected by foam and buildup

[Show Product](#)



### VEGACAP 64

Capacitive level switch as overflow protection in the silage tank

- Millimetre-precise detection of the switching point, independent of the consistency of the medium
- Reliable measurement unaffected by buildup and foam
- Long service life and low maintenance requirement through robust construction

[Show Product](#)



### VEGA Inventory System

Software for data acquisition and visualisation of level data

- Easy access to live data around the clock
- Accurate, up-to-date information on tank levels
- Simplified management through a wide range of functions
- Fully automatic and timely notification of re-supply requirements
- Increased security of supply

[Show Product](#)



PRO

### VEGAPULS 6X

[Show Product](#)



**Measuring range - Distance**  
120 m

**Process temperature**  
-196 ... 450 °C

**Process pressure**  
-1 ... 160 bar

**Accuracy**  
± 1 mm

**Frequency**  
6 GHz  
26 GHz  
80 GHz

**Beam angle**  
≥ 3°

**Materials, wetted parts**  
PTFE  
PVDF  
316L  
PP  
PEEK

**Threaded connection**  
≥ G¾, ≥ ¾ NPT

**Flange connection**  
≥ DN20, ≥ ¾"

**Hygienic fittings**  
Clamp ≥ 1½" - DIN32676, ISO2852  
Slotted nut ≥ 2", DN50 - DIN 11851  
Varivent ≥ DN25  
hygienic fitting with tension flange DN32  
hygienic fitting F40 with compression nut  
Hygienic screw connections ≥ DN50 tube ø53 -  
DIN11864-1-A  
Hygienic flange connection ≥ DN50 DIN11864-2  
Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-  
3-A  
DRD connection ø 65 mm  
SMS 1145 DN51

PRO

### VEGACAP 64

[Show Product](#)



**Measuring range - Distance**  
-

**Process temperature**  
-50 ... 200 °C

**Process pressure**  
-1 ... 64 bar

**Version**  
PTFE insulation

**Materials, wetted parts**  
PTFE  
316L  
Alloy C22 (2.4602)  
Steel C22.8

**Threaded connection**  
≥ G¾, ≥ ¾ NPT

**Flange connection**  
≥ DN25, ≥ 1"

**Seal material**  
no media contact

**Housing material**  
Plastic  
Aluminium  
Stainless steel (precision casting)  
Stainless steel (electropolished)

**Protection rating**  
IP66/IP68 (0,2 bar)  
IP66/IP67  
IP66/IP68 (1 bar)

### VEGA Inventory System

[Show Product](#)

