



Reliable

Reliable filling with overflow protection and leak sensors

Cost effective

Maximum utilization of the container volume thanks to continuous level measurement

User friendly


Direct reading of the measured value at the additive station

Storage tank for wet strength agent

Level measurement and point level detection in the storage tank for wet strength agent

Wet strength agents are polymeric additives that increase the water resistance particularly of hygienic and specialty papers. These are applied in the paper machine via a size press or spraying device. Because of their high pH value, these substances are stored in double-walled GRP (glass reinforced plastic) tanks. For safety and operational reasons, multiple level measurements are needed in these tanks.

[More details](#)



VEGAPULS 31

Level measurement with radar in the wet-strength agent storage tank

- Exact measurement, unaffected by temperature and medium composition
- High measuring accuracy even at low filling levels
- Maintenance free, thanks to a non-contact level measurement

[Show Product](#)



VEGASWING 63

Vibrating level switch as overflow protection in the storage tank

- Simple function test via keystroke
- WHG-approved instrument provides legal certainty

[Show Product](#)

BASIC

VEGAPULS 31
[Show Product](#)

Measuring range - Distance
 15 m

Process temperature
 -40 ... 80 °C

Process pressure
 -1 ... 3 bar

Accuracy
 ± 2 mm

Frequency
 80 GHz

Beam angle
 8°

Materials, wetted parts
 PVDF

Threaded connection
 G1½, 1½ NPT, R1½

Seal material
 FKM

Housing material
 Plastic

PRO

VEGASWING 63
[Show Product](#)

Process temperature
 -50 ... 250 °C

Process pressure
 -1 ... 64 bar

Version
 Standard
 Hygienic applications
 with gas-tight leadthrough
 with tube extension
 with temperature adapter

Materials, wetted parts
 PFA
 316L
 Alloy C22 (2.4602)
 Alloy 400 (2.4360)
 ECTFE
 Enamel

Threaded connection
 ≥ G¾, ≥ ¾ NPT

Flange connection
 ≥ DN25, ≥ 1"

Hygienic fittings
 Clamp ≥ 1" - DIN32676, ISO2852
 Slotted nut ≥ 1½", ≥ DN40 - DIN 11851
 Varivent ≥ DN25
 hygienic fitting F40 with compression nut
 SMS 1145 DN51
 SMS DN38
 Hygienic fittings ≥ DN25 - DIN11864-1-A
 Hygienic flange connection DIN11864-2-A;
 DN60(ISO)ø60,3
 SMS socket piece DN38 PN6

Seal material
 no media contact

Housing material
 Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)

Protection rating
 IP66/IP67
 IP66/IP68 (1 bar)
 IP65