



Reliable

Unaffected by extreme process conditions

Cost effective

Reliable, continuous operation with absolute hygiene

User friendly


Easy adjustment and setup, as internals do not interfere

Bioreactor

Level and pressure measurement in the production of enzymes, proteins and antibodies

Some pharmaceutical companies use bioreactor vessels to cultivate particular cells or microorganisms required for certain treatments. The very high level of hygiene required means the vessels and all associated parts must be easy to thoroughly clean, because even the slightest contamination with other organisms can lead to an aborted production run. These reactors are mainly "batch-fed", where they are completely filled at the start and not emptied again until the process is completed. The pressure and level in the reactor have to be monitored continuously during process in order to obtain a high-quality yield.

More details



VEGAPULS 6X

Radar sensor for continuous level measurement in the bioreactor

- The front-flush, encapsulated antenna is easy to clean and resistant to the extreme conditions of the SIP and CIP processes
- Maximum utilization of the reactor, measurement is unaffected by changing products and process conditions
- The small beam angle and good focusing of the sensor allows easy alignment

[Show Product](#)



VEGABAR 83

Pressure transmitter for continuous pressure monitoring in the bioreactor and in the pipeline

- The welded, 50 µm-thick Alloy diaphragm with aseptic process fitting is a hygienically optimal and reliable solution
- Neither the chemical cleaning cycles nor the thermal shocks after sterilization can affect the diaphragm
- Pressure measurement in the pipeline for monitoring CIP cleaning processes

[Show Product](#)



VEGABAR 38


Pressure monitoring with IO-Link connection in the supply line of the heating medium


- Reliable measurement thanks to fast response time
- Robust ceramic CERTEC® measuring cell guarantees a long service life
- Simple operation thanks to VDMA menu structure and integrated display

[Show Product](#)

PRO
VEGAPULS 6X Show Product

Measuring range - Distance 120 m
Process temperature -196 ... 450 °C
Process pressure -1 ... 160 bar
Accuracy ± 1 mm
Frequency 6 GHz 26 GHz 80 GHz
Beam angle ≥ 3°
Materials, wetted parts PTFE PVDF 316L PP PEEK
Threaded connection ≥ G¾, ≥ ¾ NPT
Flange connection ≥ DN20, ≥ ¾"
Hygienic fittings Clamp ≥ 1½" - DIN32676, ISO2852 Slotted nut ≥ 2", DN50 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 hygienic fitting F40 with compression nut Hygienic screw connections ≥ DN50 tube ø53 - DIN11864-1-A Hygienic flange connection ≥ DN50 DIN11864-2 Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A DRD connection ø 65 mm SMS 1145 DN51

PRO
VEGABAR 83 Show Product

Measuring range - Distance -
Measuring range - Pressure -1 ... 1000 bar
Process temperature -40 ... 200 °C
Process pressure -1 ... 1000 bar
Accuracy 0.075 %
Materials, wetted parts 316L Alloy C22 (2.4602) 316Ti (1.4571) Alloy C4 (2.4610)
Threaded connection ≥ G½, ≥ ½ NPT
Flange connection ≥ DN25, ≥ 1"
Hygienic fittings Slotted nut ≥ DN25 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 Hygienic flange connection ≥ DN50 DIN11864-2 SMS 1145 DN51 SMS DN38 Hygienic fittings ≥ DN33 - DIN11864-1-A Hyg. collar clamp adapter DN40PN40 DIN11864-3-A Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53 Swagelok VCR screwing Varivent G125
Seal material no media contact

BASIC
VEGABAR 38 Show Product

Measuring range - Pressure -1 ... 60 bar
Process temperature -40 ... 130 °C
Accuracy 0.3 %
Materials, wetted parts PVDF 316L Duplex (1.4462) Ceramic
Threaded connection ≥ G½, ≥ ½ NPT
Hygienic fittings Clamp ≥ 2", DN50 - DIN32676, ISO2852 Clamp ≥ 1" - DIN32676, ISO2852 Clamp ≥ 1½" - DIN32676, ISO2852 Slotted nut ≥ 1½", ≥ DN40 - DIN 11851 Slotted nut ≥ DN25 - DIN 11851 SMS DN38 Hygienic fittings ≥ DN25 - DIN11864-1-A Hygienic fittings ≥ DN40 - DIN11864-1-A Varivent N50-40 SMS DN25 Ingold connection PN10 Varivent F25
Seal material EPDM FKM FFKM
Housing material Plastic
Protection rating IP66/IP67 IP65
Output 4 ... 20 mA Three-wire (PNP/NPN, 4 ... 20 mA) IO-Link