



#### Reliable

Reliable measurement is ensured in all weather conditions

#### Cost effective

Optimum utilization of stockpile capacity

#### User friendly

Maintenance-free operation

## Bulk solids stockpile

### Level measurement of stockpiles

After being crushed, screened and sorted into different grain sizes, the gravel and sand are transported on conveyors and stored in large stockpiles. To automate the stockpiling levels and enable the optimum area to be filled, a reliable level measurement is essential.

[More details](#)



### VEGAPULS 6X

Non-contact stockpile monitoring with radar

- Reliable stockpile control, unaffected by material flow and weather conditions
- Maintenance-free operation, thanks to non-contact measurement
- Optimal monitoring of the filling process at the stockpile

[Show Product](#)



### VEGAMIP 61

Conveyor belt empty alarm with microwave barrier

- Reliable empty alarm system for conveyor belt
- Long service life, thanks to robust construction
- Unaffected by soiling and buildup

[Show Product](#)

PRO

PRO

**VEGAPULS 6X**[Show Product](#)**Measuring range - Distance**

120 m

**Process temperature**

-196 ... 450 °C

**Process pressure**

-1 ... 160 bar

**Accuracy**

± 1 mm

**Frequency**

6 GHz

26 GHz

80 GHz

**Beam angle**

≥ 3°

**Materials, wetted parts**

PTFE

PVDF

316L

PP

PEEK

**Threaded connection**

≥ G¾, ≥ ¾ NPT

**Flange connection**

≥ DN20, ≥ ¾"

**Hygienic fittings**

Clamp ≥ 1½" - DIN32676, ISO2852

Slotted nut ≥ 2", DN50 - DIN 11851

Varivent ≥ DN25

hygienic fitting with tension flange DN32

hygienic fitting F40 with compression nut

Hygienic screw connections ≥ DN50 tube ø53 -  
DIN11864-1-A

Hygienic flange connection ≥ DN50 DIN11864-2

Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-  
3-A

DRD connection ø 65 mm

SMS 1145 DN51

**VEGAMIP 61**[Show Product](#)**Measuring range - Distance**

100 m

**Process temperature**

-40 ... 80 °C

**Process pressure**

-1 ... 4 bar

**Version**

hygienically encapsulated horn antenna

for separate horn antenna

with horn antenna ø 40 mm

with horn antenna ø 48 mm

with horn antenna ø 75 mm

with horn antenna ø 95 mm

with plastic horn antenna ø 80 mm

Horn antenna ø 1½"

with encapsulated horn antenna

**Materials, wetted parts**

PTFE

316L

1.4848

PP

**Threaded connection**

G1½, 1½ NPT

**Flange connection**

≥ DN50, ≥ 2"

**Hygienic fittings**

Slotted nut ≥ 2", DN50 - DIN 11851

Varivent ≥ DN25

DRD connection ø 65 mm

for NEUMO BioControl D50 PN16 / 316L

**Seal material**

FKM

FFKM

**Housing material**

Plastic

Aluminium

Stainless steel (precision casting)

Stainless steel (electropolished)