



Reliable

Reliable measurement even during filling

Cost effective

Accurate measurement of the entire container volume

User friendly


Simple mounting and setup

Lime silo I

Level measurement and point level detection in the lime silo

For flue gas desulfurization a continuous production of the lime milk is required, the lime is kept on hand in sufficient quantities in large silos. Lime tends to readily adhere to more or less anything, depending on its type and consistency, interfering with equipment like the operation of instruments. A robust, non-susceptible level measurement is therefore absolutely necessary for reliable lime logistics and stocking. That's why a non-contact measuring instrument that also works well in the very dusty environment is essential here.

[More details](#)



VEGAPULS 6X

Non-contact level measurement with radar in the lime silo

- Non-contact, maintenance-free measurement
- High measurement certainty despite extreme dust generation
- High operational reliability, even when water condenses on instrument

[Show Product](#)



VEGAMIP 61

Non-contact point level detection with radar in the lime silo

- Non-contact, maintenance-free measurement
- Very long service life and low maintenance requirements through robust design
- Simple measurement from outside the container

[Show Product](#)

PRO

PRO

VEGAPULS 6X[Show Product](#)**Measuring range - Distance**

120 m

Process temperature

-196 ... 450 °C

Process pressure

-1 ... 160 bar

Accuracy

± 1 mm

Frequency

6 GHz

26 GHz

80 GHz

Beam angle

≥ 3°

Materials, wetted parts

PTFE

PVDF

316L

PP

PEEK

Threaded connection

≥ G¾, ≥ ¾ NPT

Flange connection

≥ DN20, ≥ ¾"

Hygienic fittings

Clamp ≥ 1½" - DIN32676, ISO2852

Slotted nut ≥ 2", DN50 - DIN 11851

Varivent ≥ DN25

hygienic fitting with tension flange DN32

hygienic fitting F40 with compression nut

Hygienic screw connections ≥ DN50 tube ø53 -
DIN11864-1-A

Hygienic flange connection ≥ DN50 DIN11864-2

Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-
3-A

DRD connection ø 65 mm

SMS 1145 DN51

VEGAMIP 61[Show Product](#)**Measuring range - Distance**

100 m

Process temperature

-40 ... 80 °C

Process pressure

-1 ... 4 bar

Version

hygienically encapsulated horn antenna

for separate horn antenna

with horn antenna ø 40 mm

with horn antenna ø 48 mm

with horn antenna ø 75 mm

with horn antenna ø 95 mm

with plastic horn antenna ø 80 mm

Horn antenna ø 1½"

with encapsulated horn antenna

Materials, wetted parts

PTFE

316L

1.4848

PP

Threaded connection

G1½, 1½ NPT

Flange connection

≥ DN50, ≥ 2"

Hygienic fittings

Slotted nut ≥ 2", DN50 - DIN 11851

Varivent ≥ DN25

DRD connection ø 65 mm

for NEUMO BioControl D50 PN16 / 316L

Seal material

FKM

FFKM

Housing material

Plastic

Aluminium

Stainless steel (precision casting)

Stainless steel (electropolished)