



#### Reliable

All materials are fully chemically resistant

#### Cost effective

Universal application, independent of product characteristics and process conditions

#### User friendly

Maintenance-free operation

## Chlorine storage tank

### Level measurement and point level detection in storage tanks for chlorine

Chlorine production and storage places high demands on the chemical and the diffusion resistance of the materials in the production equipment. Extensive process knowledge and experience is required when selecting the sealing materials. In fact it is decisive for the long-term, safe and profitable operation of the plant. Since the processes can only be interrupted at great expense and plant disruption, the reliability of the instrumentation is a top priority.

[More details](#)



#### VEGAPULS 6X

Level measurement with non-contact radar sensor in the storage tank for chlorine

- Reliable level measurement under all process conditions
- Optimum chemical resistance is ensured by a diffusion-tight, 8 mm thick PTFE disc
- Maintenance-free operation with very long service life

[Show Product](#)



#### VEGASWING 63

Point level detection with vibrating level switch in the storage tank for chlorine

- Reliable level detection under all process conditions in wide temperature and pressure ranges
- Various highly resistant materials are available to meet widely different demands on chemical resistance
- Simple function check with test button on the sensor

[Show Product](#)

PRO

## VEGAPULS 6X

[Show Product](#)



**Measuring range - Distance**  
120 m

**Process temperature**  
-196 ... 450 °C

**Process pressure**  
-1 ... 160 bar

**Accuracy**  
± 1 mm

**Frequency**  
6 GHz  
26 GHz  
80 GHz

**Beam angle**  
≥ 3°

**Materials, wetted parts**  
PTFE  
PVDF  
316L  
PP  
PEEK

**Threaded connection**  
≥ G $\frac{3}{4}$ , ≥  $\frac{3}{4}$  NPT

**Flange connection**  
≥ DN20, ≥  $\frac{3}{4}$ "

**Hygienic fittings**  
Clamp ≥ 1 $\frac{1}{2}$ " - DIN32676, ISO2852  
Slotted nut ≥ 2", DN50 - DIN 11851  
Varivent ≥ DN25  
hygienic fitting with tension flange DN32  
hygienic fitting F40 with compression nut  
Hygienic screw connections ≥ DN50 tube ø53 - DIN11864-1-A  
Hygienic flange connection ≥ DN50 DIN11864-2  
Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A  
DRD connection ø 65 mm  
SMS 1145 DN51

PRO

## VEGASWING 63

[Show Product](#)



**Process temperature**  
-50 ... 250 °C

**Process pressure**  
-1 ... 64 bar

**Version**  
Standard  
Hygienic applications  
with gas-tight leadthrough  
with tube extension  
with temperature adapter

**Materials, wetted parts**  
PFA  
316L  
Alloy C22 (2.4602)  
Alloy 400 (2.4360)  
ECTFE  
Enamel

**Threaded connection**  
≥ G $\frac{3}{4}$ , ≥  $\frac{3}{4}$  NPT

**Flange connection**  
≥ DN25, ≥ 1"

**Hygienic fittings**  
Clamp ≥ 1" - DIN32676, ISO2852  
Slotted nut ≥ 1 $\frac{1}{2}$ ", ≥ DN40 - DIN 11851  
Varivent ≥ DN25  
hygienic fitting F40 with compression nut  
SMS 1145 DN51  
SMS DN38  
Hygienic fittings ≥ DN25 - DIN11864-1-A  
Hygienic flange connection DIN11864-2-A;  
DN60(ISO)ø60,3  
SMS socket piece DN38 PN6

**Seal material**  
no media contact

**Housing material**  
Plastic  
Aluminium  
Stainless steel (precision casting)  
Stainless steel (electropolished)

**Protection rating**  
IP66/IP67  
IP66/IP68 (1 bar)  
IP65