

Reliable

High operational reliability, even with abrasive contaminants in the process medium, due to ceramic measuring cell

Cost effective

Operating the cleaner at the optimal operating point

User friendly

Minimal servicing thanks to maintenance-free measurement

Cleaner

Pressure measurement in the cleaner

Cleaners remove contaminating materials that are specifically heavier than fibres. In waste paper processing, these contaminants are, for example, sand, glass, stones or staples. The feed through the inlet is tangential in order to set the flow of material in rotation. The heavier particles migrate outwards due to the centrifugal forces and are precipitated downwards, while the lighter fibres in the middle of the vortex rise upwards and are passed on as accepted material. Pressure measurements in the inlet, outlet and overflow are required to regulate the process and ensure that it stays at the optimal operating point.

More details




VEGABAR 82

Pressure transmitter for pressure measurement in the cleaner

- Front-flush installation in the pipeline
- Robust ceramic diaphragm for long-term use
- Reliable measurement for regulating the process to the optimal operating point

Show Product





	VEGABAR 82
	Show Product
Measuring ra -	nge - Distance
Measuring ra	nge - Pressure
-1 100 bar	
Process temp	perature
-40 150 °C	-
Process pres	SUIP
-1 100 bar	0410
Accuracy 0.05 %	
Materials, we	tted parts
PVDF 316L	
Alloy C22 (2.4)	302)
PP	552)
1.4057	
1.4410	
Alloy C276 (2.4	4819)
Duplex (1.4462	2)
Titanium Grade	e 2 (3.7035)
Threaded cor	nection
≥ G½, ≥ ½ NP	Г
Flange conne	ection
≥ DN15, ≥ ½"	
Hygenic fittin	gs
Clamp ≥ 1" - D	IN32676, ISO2852
Slotted nut ≥ D	N25 - DIN 11851
hygienic fitting	with tension flange DN32
	F40 with compression nut
DRD connection	
SMS 1145 DN SMS DN38	51
SMS DN38 Swagelok VCF	2 screwing
Varivent G125	(Solowing
Varivent N50-4	0
for NEUMO Bi	oControl D50 PN16 / 316L
Seal material	
EPDM	
FKM	

FKM FFKM

