

#### Reliable

High supply reliability through dependable measurement

Cost effective Maintenance-free operation


User friendly Simple mounting and parameterization

# Elevated storage tanks

### Level measurement in the elevated tank

Elevated water tanks are reservoirs located at high places that act as a buffer during periods of peak demand. They compensate for delivery fluctuations and enable efficient plant operation. Reliable level measurement is therefore indispensable.

### More details





#### **VEGAPULS C 22**

Non-contact level measurement with radar in the elevated tank

- Reliable, water proof and unaffected by condensation
- Maintenance-free operation through non-contact measurement
- Secure, user-friendly wireless operation via Bluetooth with smartphone, tablet or PC
- Simple installation with additional mounting accessories

# Show Product

## VEGADIS 82

External display and adjustment unit for 4 ... 20 mA/HART sensors

- Measured value display can be connected anywhere along the supply cable of the sensor.
- Easy-to-read display with plain text and graphics
- Simple operation via four keys and clearly structured menu

## **Show Product**



#### BASIC

| Briefe                                 |                               |  |
|--|-------------------------------|--|
|  | VEGAPULS C 22<br>Show Product |  |
|  |                               |  |
| Measuring range - Distance<br>15 m     |                               | Housing material<br>Plastic<br>Aluminium |
| Process temperature<br>-40 80 °C       |                               | Stainless steel (pre                     |
| Process pressure<br>-1 3 bar           |                               | IP66/IP67                                |
| Accuracy<br>± 2 mm                     |                               | -20 70 °C                                |
| Frequency<br>80 GHz                    |                               | Signal input (spec                       |
| <b>Beam angle</b><br>8°                |                               |  |
| <b>Materials, wetted parts</b><br>PVDF |                               |  |
| <b>Threaded con</b><br>G1½, 1½ NPT, I  |                               |  |
| <b>Seal material</b><br>FKM            |                               |  |
| Housing material<br>Housing material   |                               |  |
|  |                               |  |

| VEGADIS 82<br>Show Product  |
|---|
|   |
| Housing material<br>Plastic<br>Aluminium<br>Stainless steel (precision casting) |
| Protection rating<br>P66/IP67   |
| Ambient temperature<br>20 70 °C   |
| Signal input (specify)  |

