



#### Reliable

High measuring accuracy despite low dielectric constants

#### Cost effective

Maintenance-free operation

#### User friendly

Easy installation and setup

## Propane storage in bullets and spheres

### Level measurement and pressure monitoring of liquefied gases in storage

Propane, a flammable, colourless and odourless gas, is one of the many types of liquefied petroleum gases (LPG) that exist. It is produced from natural gas via a special refining process. Propane is compressed, liquefied and stored in pressure vessels so that it does not return to a gaseous state. To ensure optimal storage, reliable level measurement is required.

[More details](#)



#### VEGABAR 83

Pressure transmitter for pressure monitoring in spherical tanks

- Universally applicable, fully welded measuring cells for direct connection to process
- A variety of process fittings always enables an appropriate adaptation to the container
- SIL conformity in accordance with IEC 61508, in a single-channel architecture up to SIL2 and in a multi-channel architecture up to SIL3
- Extremely robust measuring cells of Alloy, for higher safety during operation

[Show Product](#)



#### VEGAPULS 6X

Level measurement with radar in spherical tanks

- Maintenance-free operation thanks to non-contact measuring principle
- High measuring accuracy even with low dielectric constants
- Very narrow signal focusing even in large measuring ranges
- The sensor is simple and easy to replace thanks to cut-off valve and isolation from process

[Show Product](#)

PRO

**VEGABAR 83**  
[Show Product](#)

**Measuring range - Distance**

-

**Measuring range - Pressure**

-1 ... 1000 bar

**Process temperature**

-40 ... 200 °C

**Process pressure**

-1 ... 1000 bar

**Accuracy**

0.075 %

**Materials, wetted parts**

316L  
 Alloy C22 (2.4602)  
 316Ti (1.4571)  
 Alloy C4 (2.4610)

**Threaded connection**

≥ G½, ≥ ½ NPT

**Flange connection**

≥ DN25, ≥ 1"

**Hygienic fittings**

Slotted nut ≥ DN25 - DIN 11851  
 Varivent ≥ DN25  
 hygienic fitting with tension flange DN32  
 Hygienice flange connection ≥ DN50 DIN11864-2  
 SMS 1145 DN51  
 SMS DN38  
 Hygienic fittings ≥ DN33 - DIN11864-1-A  
 Hyg. collar clamp adapter DN40PN40 DIN11864-3-A  
 Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53  
 Swagelok VCR screwing  
 Varivent G125

**Seal material**

no media contact

PRO

**VEGAPULS 6X**  
[Show Product](#)

**Measuring range - Distance**

120 m

**Process temperature**

-196 ... 450 °C

**Process pressure**

-1 ... 160 bar

**Accuracy**

± 1 mm

**Frequency**

6 GHz  
 26 GHz  
 80 GHz

**Beam angle**

≥ 3°

**Materials, wetted parts**

PTFE  
 PVDF  
 316L  
 PP  
 PEEK

**Threaded connection**

≥ G¾, ≥ ¾ NPT

**Flange connection**

≥ DN20, ≥ ¾"

**Hygienic fittings**

Clamp ≥ 1½" - DIN32676, ISO2852  
 Slotted nut ≥ 2", DN50 - DIN 11851  
 Varivent ≥ DN25  
 hygienic fitting with tension flange DN32  
 hygienic fitting F40 with compression nut  
 Hygienic screw connections ≥ DN50 tube ø53 -  
 DIN11864-1-A  
 Hygienice flange connection ≥ DN50 DIN11864-2  
 Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-  
 3-A  
 DRD connection ø 65 mm  
 SMS 1145 DN51