



Reliable

High measuring accuracy despite low dielectric constants

Cost effective

Maintenance-free operation

User friendly

Easy installation and setup

Propane storage in bullets and spheres

Level measurement and pressure monitoring of liquefied gases in storage

Propane, a flammable, colourless and odourless gas, is one of the many types of liquefied petroleum gases (LPG) that exist. It is produced from natural gas via a special refining process. Propane is compressed, liquefied and stored in pressure vessels so that it does not return to a gaseous state. To ensure optimal storage, reliable level measurement is required.

[More details](#)



VEGABAR 83

Pressure transmitter for pressure monitoring in spherical tanks

- Universally applicable, fully welded measuring cells for direct connection to process
- A variety of process fittings always enables an appropriate adaptation to the container
- SIL conformity in accordance with IEC 61508, in a single-channel architecture up to SIL2 and in a multi-channel architecture up to SIL3
- Extremely robust measuring cells of Alloy, for higher safety during operation

[Show Product](#)



VEGAPULS 6X

Level measurement with radar in spherical tanks

- Maintenance-free operation thanks to non-contact measuring principle
- High measuring accuracy even with low dielectric constants
- Very narrow signal focusing even in large measuring ranges
- The sensor is simple and easy to replace thanks to cut-off valve and isolation from process

[Show Product](#)

PRO

VEGABAR 83

[Show Product](#)



Measuring range - Distance

-

Measuring range - Pressure

-1 ... 1000 bar

Process temperature

-40 ... 200 °C

Process pressure

-1 ... 1000 bar

Accuracy

0.075 %

Materials, wetted parts

316L
Alloy C22 (2.4602)
316Ti (1.4571)
Alloy C4 (2.4610)

Threaded connection

≥ G½, ≥ ½ NPT

Flange connection

≥ DN25, ≥ 1"

Hygienic fittings

Slotted nut ≥ DN25 - DIN 11851
Varivent ≥ DN25
hygienic fitting with tension flange DN32
Hygienice flange connection ≥ DN50 DIN11864-2
SMS 1145 DN51
SMS DN38
Hygienic fittings ≥ DN33 - DIN11864-1-A
Hyg. collar clamp adapter DN40PN40 DIN11864-3-A
Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53
Swagelok VCR screwing
Varivent G125

Seal material

no media contact

PRO

VEGAPULS 6X

[Show Product](#)



Measuring range - Distance

120 m

Process temperature

-196 ... 450 °C

Process pressure

-1 ... 160 bar

Accuracy

± 1 mm

Frequency

6 GHz
26 GHz
80 GHz

Beam angle

≥ 3°

Materials, wetted parts

PTFE
PVDF
316L
PP
PEEK

Threaded connection

≥ G¾, ≥ ¾ NPT

Flange connection

≥ DN20, ≥ ¾"

Hygienic fittings

Clamp ≥ 1½" - DIN32676, ISO2852
Slotted nut ≥ 2", DN50 - DIN 11851
Varivent ≥ DN25
hygienic fitting with tension flange DN32
hygienic fitting F40 with compression nut
Hygienic screw connections ≥ DN50 tube ø53 -
DIN11864-1-A
Hygienice flange connection ≥ DN50 DIN11864-2
Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-
3-A
DRD connection ø 65 mm
SMS 1145 DN51