

#### Reliable


Reliable measurement of the level

# **Cost effective**

Maintenance-free measurement with high accuracy

# **User friendly**

Reliable, continuous operation



# Oil feed tank

# Turbine oil feed tank level measurement

Turbines are highly complex systems in which lubricating oil plays an important role. The oil is used to ensure proper operation, to reduce maintenance costs to a minimum and to prevent turbine failure. Turbine oils are produced from high quality mineral oils that have special properties to reduce demulsification (separation of water) and air release. The level in the feed tank must be monitored to ensure that there is always enough oil available for lubrication.

#### More details



# **VEGAFLEX 81**

Level measurement with guided radar for reliable data on the oil level in the turbine

- Reliable, maintenance-free measurement
- High measurement certainty, even with heavy buildup
- Modern measuring technique guarantees high operational reliability

**Show Product** 



#### PRO

# **VEGAFLEX 81**

#### **Show Product**



#### Measuring range - Distance

#### Process temperature

-60 ... 200 °C

## Process pressure

-1 ... 40 bar

# Accuracy

±2 mm

#### Version

Basic version for exchangeable cable ø 2; ø 4 mm Basic version for exchangeable rod ø 8 mm Basic version for exchangeable rod ø 12 mm

Coax version ø 21.3 mm for ammonia application

Coax version ø 21.3 mm with single hole

Coax version ø 21.3 mm with multiple hole

Coax version ø 42.2 mm with multiple hole

Exchangeable rod ø 8 mm

Exchangeable rod ø 12 mm

Exchangeable cable ø 2 mm with gravity weight Exchangeable cable ø 4 mm with gravity weight Exchangeable cable ø 2 mm with centering weight Exchangeable cable ø 4 mm with centering weight Exchangeable cable ø 4 mm without weight exchangeable, PFA-coated cable ø4 mm with non-coated centering weight

# Materials, wetted parts

PFA

316L

Alloy C22 (2.4602)

Alloy 400 (2.4360)

Alloy C276 (2.4819)

Duplex (1.4462)

304L

# Threaded connection

≥ G¾, ≥ ¾ NPT

# Flange connection

≥ DN25, ≥ 1"

#### Seal material

EPDM

FKM FFKM

Silicone FEP coated

Borosilicate glass

# Housing material

Plastic

Aluminium

Stainless steel (precision casting)

Stainless steel (electropolished)

