



Reliable

Measurement independent of changing process conditions

Cost effective

Low maintenance requirements reduce downtime and costs

User friendly


Broad range of process fittings allows easy retrofitting

Amine contactor

Level and pressure measurement of high pressure amine contactor

Amine contactors introduce amine solutions to the incoming natural gas from the inlet separator to remove acidic components, such as H₂S and CO₂, from the process stream. The operator must accurately monitor the amine collecting at the bottom of the contactor to ensure that the process is running efficiently.

[More details](#)



VEGAFLEX 86

Continuous level measurement with guided wave radar in amine contactors

- Non-moving parts are immune to mechanical failure
- Robust mechanical construction is resistant to extreme process conditions
- Measures accurately unaffected by changing gravity, temperature or pressure

[Show Product](#)



VEGABAR 81

Pressure transmitter for pressure monitoring in amine contactors

- Isolated diaphragm increases temperature resistance
- Tough diaphragm materials provide excellent chemical resistance
- Easy mechanical adaption thanks to large selection of flange and tube versions

[Show Product](#)

PRO

PRO

VEGAFLEX 86
[Show Product](#)

Measuring range - Distance
 75 m

Process temperature
 -196 ... 450 °C

Process pressure
 -1 ... 400 bar

Accuracy
 ± 2 mm

Version
 Coax version ø 21.3 mm with multiple hole
 Coax version ø 42.2 mm with single hole
 Coax version ø 42.2 mm with multiple hole
 Exchangeable rod ø 16 mm
 Exchangeable cable ø 2 mm with gravity weight
 Exchangeable cable ø 4 mm with gravity weight
 Exchangeable cable ø 2 mm with centering weight
 Exchangeable cable ø 4 mm with centering weight

Materials, wetted parts
 316L
 Alloy C22 (2.4602)
 316

Threaded connection
 ≥ G¾, ≥ ¼ NPT

Flange connection
 ≥ DN25, ≥ 1"

Seal material
 FFKM
 graphit and ceramic

Housing material
 Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)

VEGABAR 81
[Show Product](#)

Measuring range - Distance
 -

Measuring range - Pressure
 -1 ... 1000 bar

Process temperature
 -90 ... 400 °C

Process pressure
 -1 ... 1000 bar

Accuracy
 0.2 %
 0.1 %

Materials, wetted parts
 Alloy C22 (2.4602)
 Alloy 400 (2.4360)
 Tantalum
 Alloy C276 (2.4819)
 Duplex (1.4462)
 Titanium Grade 2 (3.7035)
 1.4435
 316/316L
 Titanium Grade 7 (3.7235)

Threaded connection
 ≥ G½, ≥ ½ NPT

Flange connection
 ≥ DN25, ≥ 1"

Hygienic fittings
 Clamp ≥ 1" - DIN32676, ISO2852
 Slotted nut ≥ 1½", ≥ DN40 - DIN 11851
 hygienic fitting with tension flange DN32
 hygienic fitting F40 with compression nut
 Hygienice flange connection ≥ DN50 DIN11864-2
 Hygienic fittings ≥ DN40 - DIN11864-1-A

Seal material
 no media contact