



Reliable

Reliable function even during filling

Cost effective

Dry run protection prevents failures or damage to the eccentric pumps

User friendly

Easy alignment via optional adjustable sealing gaskets

Starch silo

Level measurement in starch silos and dry run protection for starch liquefaction vessels

Starch is an important additive to increase the strength of the paper. The raw starch is stored in tall, narrow silos. Filling is carried out pneumatically, generating large amounts of dust. They are discharged into the starch slurry production system beneath the silo and the resulting slurry is pumped into the starch cookers by eccentric pumps. For optimal control of the silo filling process, a reliable level measurement is required. To prevent the eccentric pump from running dry, an in-line switch is needed upstream of the pump.

[More details](#)



VEGAPULS 6X

Level measurement with radar in the starch silo

- Maintenance-free operation through non-contact measuring method
- Precise alignment and measurement even in high, narrow Silos
- Reliable measurement despite dust

[Show Product](#)



VEGASWING 61

Vibrating level switch as a universal dry run protection for eccentric pumps

- Small process fittings, short fork also suitable for small pipe diameters
- Easy setup and commissioning because adjustment-free
- Reliable measurement thanks to product-independent switching point

[Show Product](#)

PRO

PRO

VEGAPULS 6X
[Show Product](#)

Measuring range - Distance
 120 m

Process temperature
 -196 ... 450 °C

Process pressure
 -1 ... 160 bar

Accuracy
 ± 1 mm

Frequency
 6 GHz
 26 GHz
 80 GHz

Beam angle
 ≥ 3°

Materials, wetted parts
 PTFE
 PVDF
 316L
 PP
 PEEK

Threaded connection
 ≥ G¾, ≥ ¾ NPT

Flange connection
 ≥ DN20, ≥ ¾"

Hygienic fittings
 Clamp ≥ 1½" - DIN32676, ISO2852
 Slotted nut ≥ 2", DN50 - DIN 11851
 Varivent ≥ DN25
 hygienic fitting with tension flange DN32
 hygienic fitting F40 with compression nut
 Hygienic screw connections ≥ DN50 tube ø53 -
 DIN11864-1-A
 Hygienic flange connection ≥ DN50 DIN11864-2
 Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-
 3-A
 DRD connection ø 65 mm
 SMS 1145 DN51

VEGASWING 61
[Show Product](#)

Measuring range - Distance
 -

Process temperature
 -50 ... 250 °C

Process pressure
 -1 ... 64 bar

Version
 Standard
 Hygienic applications
 with gas-tight leadthrough
 with temperature adapter

Materials, wetted parts
 PFA
 316L
 Alloy C22 (2.4602)
 Alloy 400 (2.4360)
 ECTFE
 Enamel

Threaded connection
 ≥ G¾, ≥ ¾ NPT

Flange connection
 ≥ DN25, ≥ 1"

Hygienic fittings
 Clamp ≥ 1" - DIN32676, ISO2852
 Slotted nut ≥ 1½", ≥ DN40 - DIN 11851
 Varivent ≥ DN25
 hygienic fitting F40 with compression nut
 SMS 1145 DN51
 SMS DN38
 Hygienic fittings ≥ DN25 - DIN11864-1-A
 Hygienic flange connection DIN11864-2-A;
 DN60(ISO)ø60,3
 SMS socket piece DN38 PN6

Seal material
 no media contact

Housing material
 Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)