



Reliable

Redundant measurement for maximum security

Cost effective

No additional process fittings on the tank necessary

User friendly


Maintenance-free and reliable in operation

Storage tanks for highly toxic liquids

Level measurement and point level detection in highly toxic media

For extremely toxic substances such as phosgene, absolute control over the process is a necessity. In industrial applications, these products are only used in hermetically closed circuits. To minimize the inherent risks, independent protection devices form an integral part of the tank equipment. Moreover, it is important to keep the number of tank openings as small as possible. An external level measuring system that includes point level detection is ideal for such situations.

More details



SOLITRAC 31

Radiation-based sensor for continuous level measurement in storage tanks for highly toxic substances

- Maximum safety and process integrity, regardless of media properties
- No container opening required, the measurement is carried out on the outside of the tank
- Maintenance-free operation, no wetted parts

[Show Product](#)



MINITRAC 31

Radiation-based level detection for overflow or dry run protection in storage tanks for highly toxic substances

- Reliable monitoring of the minimum or maximum level, independent of media properties
- No container opening required, the measurement is carried out from the outside through the container wall
- Maintenance-free operation, no wetted parts

[Show Product](#)



VEGASOURCE 82

The source holder is used to hold and secure the radioactive source

- Small footprint and simple installation
- Operational reliability through pneumatic opening and closing of the source container
- Trustworthy shielding allows use without control area

[Show Product](#)

PRO

SOLITRAC 31
[Show Product](#)



Measuring range - Distance
 3 m

Process pressure
 -

Accuracy
 ± 0.5 %

Materials, wetted parts
 No wetted material

Seal material
 no media contact

Housing material
 Aluminium
 Stainless steel (precision casting)

Protection rating
 IP66/IP67

Output
 Profibus PA
 Foundation Fieldbus
 Four-wire: 4 ... 20 mA/HART

Ambient temperature
 -40 ... 60 °C

PRO

MINITRAC 31
[Show Product](#)



Measuring range - Distance
 -

Process pressure
 -

Accuracy
 0.1 %

Materials, wetted parts
 No wetted material

Seal material
 no media contact

Housing material
 Aluminium
 Stainless steel (precision casting)

Protection rating
 IP66/IP67

Output
 Profibus PA
 Foundation Fieldbus
 Four-wire: 4 ... 20 mA/HART

Ambient temperature
 -40 ... 60 °C

VEGASOURCE 82
[Show Product](#)

