

#### Reliable

Ensures the supply of salt

#### Cost effective

Efficient and simple planning of deliveries

### User friendly

Simple installation and commissioning



# Salt silo

# Level measurement in the road salt silo

During the winter season the highways and road maintenance departments safeguard the roads, public squares and pedestrian paths by clearing off snow and ice. The quantities of road salt required are stored in silos and when needed, loaded onto snowploughs. Reliable level measurement is necessary for the optimal and adequate stocking of the salt. The stock level information is transmitted to the central control centre.

# More details



# VEGAPULS Air 42

Road salt silo inventory measurement with autarkic radar level sensor

- Precise measurement data is maintained, despite extreme dust generation and deposits on the sensor face
- Simple retrofitting and installation is facilitated by battery power and wireless communication technology
- Reliable measured values ensure optimal and timely resupply

# **Show Product**



Software for acquisition and visualization of level data.

- Easy access to live data around the clock
- Accurate, up-to-date information on filling levels
- Numerous functions simplify inventory management
- Fully automatic and timely notification of replenishment requirements
- Increased security of supply

### **Show Product**



#### AIR

| VEGAPULS Air 42<br>Show Product | VEGA Inventory System<br>Show Product |
|---------------------------------|---------------------------------------|
| KEEN                            |                                       |
| Measuring range - Distance      | L                                     |
| 30 m                            |                                       |
| Process temperature             |                                       |
| -20 60 °C                       |                                       |
| Process pressure                |                                       |
| -1 2 bar                        |                                       |
| Accuracy                        |                                       |
| ± 2 mm                          |                                       |
| Frequency                       |                                       |
| 80 GHz                          |                                       |
| Beam angle                      |                                       |
| 4°                              |                                       |
| Materials, wetted parts         |                                       |
| PVDF                            |                                       |
| Flange connection               |                                       |
| ≥ DN80                          |                                       |
| Seal material                   |                                       |
| EPDM                            |                                       |
| FKM                             |                                       |
| Housing material                |                                       |
| Plastic                         |                                       |

