

**Reliable**

Reliable measurement, even in abrasive media

**Cost effective**

Standard sensors for all applications

**User friendly**

Simple setup and low maintenance

## Storage silo for sugar and flour

### Level and pressure measurement in storage silos

Flour and sugar are the basic ingredients for many food products and stored in silos up to 20 metres high. The filling and emptying is often performed by pneumatic systems that transport the media from the large external silos and deposit them in smaller holding vessels for further processing. The filling and emptying processes are controlled by reliable level measurement. Pressure monitoring is also needed in the pneumatic conveying pipelines.

[More details](#)



#### VEGAPULS 6X

Radar sensor for level measurement in the flour and sugar silos

- Precise focusing of the measurement signal, which means convenient installation almost anywhere on the silo roof is possible
- Accurate, reliable measurement data despite dust and noise
- Measurement even during filling, thereby ensuring continuous monitoring of the filling process via a control system

[Show Product](#)





#### VEGABAR 82

Pressure transmitter for monitoring pressure in the conveyor pipeline

- Wear-resistant CERTEC® ceramic measuring cell, insensitive to abrasion
- Maintenance-free through front-flush mounting
- Robust measuring cell for long service life

[Show Product](#)

PRO	PRO
<b>VEGAPULS 6X</b> <a href="#">Show Product</a>	<b>VEGABAR 82</b> <a href="#">Show Product</a>
	
<b>Measuring range - Distance</b> 120 m	<b>Measuring range - Distance</b> -
<b>Process temperature</b> -196 ... 450 °C	<b>Measuring range - Pressure</b> -1 ... 100 bar
<b>Process pressure</b> -1 ... 160 bar	<b>Process temperature</b> -40 ... 150 °C
<b>Accuracy</b> ± 1 mm	<b>Process pressure</b> -1 ... 100 bar
<b>Frequency</b> 6 GHz 26 GHz 80 GHz	<b>Accuracy</b> 0.05 %
<b>Beam angle</b> ≥ 3°	<b>Materials, wetted parts</b> PVDF 316L Alloy C22 (2.4602) PP 1.4057 1.4410 Alloy C276 (2.4819) Duplex (1.4462) Titanium Grade 2 (3.7035)
<b>Materials, wetted parts</b> PTFE PVDF 316L PP PEEK	
<b>Threaded connection</b> ≥ G¾, ≥ ¾ NPT	
<b>Flange connection</b> ≥ DN20, ≥ ¾"	<b>Threaded connection</b> ≥ G½, ≥ ½ NPT
<b>Hygienic fittings</b> Clamp ≥ 1½" - DIN32676, ISO2852 Slotted nut ≥ 2", DN50 - DIN 11851 Varivent ≥ DN25 hygienic fitting with tension flange DN32 hygienic fitting F40 with compression nut Hygienic screw connections ≥ DN50 tube ø53 - DIN11864-1-A Hygienic flange connection ≥ DN50 DIN11864-2 Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A DRD connection ø 65 mm SMS 1145 DN51	<b>Flange connection</b> ≥ DN15, ≥ ½"
	<b>Hygienic fittings</b> Clamp ≥ 1" - DIN32676, ISO2852 Slotted nut ≥ DN25 - DIN 11851 hygienic fitting with tension flange DN32 hygienic fitting F40 with compression nut DRD connection ø 65 mm SMS 1145 DN51 SMS DN38 Swagelok VCR screwing Varivent G125 Varivent N50-40 for NEUMO BioControl D50 PN16 / 316L
	<b>Seal material</b> EPDM FKM FFKM