



#### Reliable

Reliable measurement, independent of the process conditions

#### Cost effective

Ensures effective processing of the drilling mud

#### User friendly

Simple installation and setup from above

## Shaker

### Level measurement and point level detection in the shaker

Through the effects of strong vibration in the shaker, the liquid and solid components of the drilling mud returning from the borehole are separated from each other. The drilled rock and the sand are disposed of and the valuable drilling mud is fed back into the continuous drilling process. Level measurement and point level detection are absolutely necessary for effective processing of the drilling mud in the shaker.

[More details](#)



#### VEGAPULS 6X

Non-contact level measurement with radar in the shaker

- Accurate measurement, independent of media properties
- Reliable measurement, unaffected by vibration and buildup
- High equipment availability, as wear and maintenance-free

[Show Product](#)



#### VEGACAP 65

Capacitive level switch for point level detection in the shaker

- Long service life thanks to robust mechanical construction
- Reliable switching point ensured by large gravity weight
- Maintenance-free operation, as non-sensitive to soiling

[Show Product](#)

PRO

## VEGAPULS 6X

[Show Product](#)



**Measuring range - Distance**  
120 m

**Process temperature**  
-196 ... 450 °C

**Process pressure**  
-1 ... 160 bar

**Accuracy**  
± 1 mm

**Frequency**  
6 GHz  
26 GHz  
80 GHz

**Beam angle**  
≥ 3°

**Materials, wetted parts**  
PTFE  
PVDF  
316L  
PP  
PEEK

**Threaded connection**  
≥ G¾, ≥ ¾ NPT

**Flange connection**  
≥ DN20, ≥ ¾"

**Hygienic fittings**  
Clamp ≥ 1½" - DIN32676, ISO2852  
Slotted nut ≥ 2", DN50 - DIN 11851  
Varivent ≥ DN25  
hygienic fitting with tension flange DN32  
hygienic fitting F40 with compression nut  
Hygienic screw connections ≥ DN50 tube ø53 -  
DIN11864-1-A  
Hygienic flange connection ≥ DN50 DIN11864-2  
Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-  
3-A  
DRD connection ø 65 mm  
SMS 1145 DN51

PRO

## VEGACAP 65

[Show Product](#)



**Measuring range - Distance**  
-

**Process temperature**  
-50 ... 200 °C

**Process pressure**  
-1 ... 64 bar

**Version**  
Cable ø 6 mm with screening tube without weight  
Cable ø 6 mm with screening tube and gravity weight  
Cable ø 6 mm with gravity weight  
Cable ø 8 mm with abrasion protection without weight  
Cable ø 8 mm with abrasion protection and gravity weight  
Cable ø 8 mm with gravity weight  
PA cable ø 12 mm with screening tube and gravity weight

**Materials, wetted parts**  
PTFE  
316L  
PA  
PEEK  
Steel

**Threaded connection**  
≥ G1, ≥ 1 NPT

**Flange connection**  
≥ DN50, ≥ 2"

**Housing material**  
Plastic  
Aluminium  
Stainless steel (precision casting)  
Stainless steel (electropolished)

**Protection rating**  
IP66/IP68 (0,2 bar)  
IP66/IP67  
IP66/IP68 (1 bar)

**Output**  
Relay (DPDT)  
Contactless electronic switch  
Transistor (NPN/PNP)  
Two-wire