



#### Reliable

Approved materials in compliance with FDA and EC 1935/2004

#### Cost effective

Simple, fast setup

#### User friendly

Simple mounting

## Hexane storage tank

### Level measurement and point level detection in hexane storage tank

In pharmaceutical production, Hexane is a commonly used solvent and reaction medium, as well as an agent for oil and grease extraction. This colourless liquid has a slight petrol odour and is highly volatile light hydrocarbon, readily forming highly flammable vapour-air mixtures. When the tank is emptied, no residues may remain inside. Reliable level measurement and overflow protection is an absolute necessity for safe storage and handling.

[More details](#)



#### VEGAPULS 6X

Non-contact radar level measurement in hexane storage tank

- Measurement down to the tank bottom, even in media with low dielectric constant
- Strong focusing of the radar beam allows exact measurement
- Easy installation thanks to small process fittings

[Show Product](#)



#### VEGASWING 63

Vibrating level switch for point level detection in hexane storage tank

- Accurate level detection thanks to adjustment-free, media-independent switching point
- An enamel coating guarantees a long service life for the sensor and protects it against corrosive media
- Test button for easy testing of instrument functionality during operation

[Show Product](#)

PRO

## VEGAPULS 6X

[Show Product](#)



**Measuring range - Distance**  
120 m

**Process temperature**  
-196 ... 450 °C

**Process pressure**  
-1 ... 160 bar

**Accuracy**  
± 1 mm

**Frequency**  
6 GHz  
26 GHz  
80 GHz

**Beam angle**  
≥ 3°

**Materials, wetted parts**  
PTFE  
PVDF  
316L  
PP  
PEEK

**Threaded connection**  
≥ G¾, ≥ ¾ NPT

**Flange connection**  
≥ DN20, ≥ ¾"

**Hygienic fittings**  
Clamp ≥ 1½" - DIN32676, ISO2852  
Slotted nut ≥ 2", DN50 - DIN 11851  
Varivent ≥ DN25  
hygienic fitting with tension flange DN32  
hygienic fitting F40 with compression nut  
Hygienic screw connections ≥ DN50 tube ø53 - DIN11864-1-A  
Hygienic flange connection ≥ DN50 DIN11864-2  
Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A  
DRD connection ø 65 mm  
SMS 1145 DN51

PRO

## VEGASWING 63

[Show Product](#)



**Process temperature**  
-50 ... 250 °C

**Process pressure**  
-1 ... 64 bar

**Version**  
Standard  
Hygienic applications  
with gas-tight leadthrough  
with tube extension  
with temperature adapter

**Materials, wetted parts**  
PFA  
316L  
Alloy C22 (2.4602)  
Alloy 400 (2.4360)  
ECTFE  
Enamel

**Threaded connection**  
≥ G¾, ≥ ¾ NPT

**Flange connection**  
≥ DN25, ≥ 1"

**Hygienic fittings**  
Clamp ≥ 1" - DIN32676, ISO2852  
Slotted nut ≥ 1½", ≥ DN40 - DIN 11851  
Varivent ≥ DN25  
hygienic fitting F40 with compression nut  
SMS 1145 DN51  
SMS DN38  
Hygienic fittings ≥ DN25 - DIN11864-1-A  
Hygienic flange connection DIN11864-2-A;  
DN60(ISO)ø60,3  
SMS socket piece DN38 PN6

**Seal material**  
no media contact

**Housing material**  
Plastic  
Aluminium  
Stainless steel (precision casting)  
Stainless steel (electropolished)

**Protection rating**  
IP66/IP67  
IP66/IP68 (1 bar)  
IP65