



Reliable

Approved materials in compliance with FDA and EC 1935/2004

Cost effective

Simple, fast setup

User friendly

Simple mounting

Hexane storage tank

Level measurement and point level detection in hexane storage tank

In pharmaceutical production, Hexane is a commonly used solvent and reaction medium, as well as an agent for oil and grease extraction. This colourless liquid has a slight petrol odour and is highly volatile light hydrocarbon, readily forming highly flammable vapour-air mixtures. When the tank is emptied, no residues may remain inside. Reliable level measurement and overflow protection is an absolute necessity for safe storage and handling.

[More details](#)



VEGAPULS 6X

Non-contact radar level measurement in hexane storage tank

- Measurement down to the tank bottom, even in media with low dielectric constant
- Strong focusing of the radar beam allows exact measurement
- Easy installation thanks to small process fittings

[Show Product](#)



VEGASWING 63

Vibrating level switch for point level detection in hexane storage tank

- Accurate level detection thanks to adjustment-free, media-independent switching point
- An enamel coating guarantees a long service life for the sensor and protects it against corrosive media
- Test button for easy testing of instrument functionality during operation

[Show Product](#)

PRO

VEGAPULS 6X

[Show Product](#)



Measuring range - Distance
120 m

Process temperature
-196 ... 450 °C

Process pressure
-1 ... 160 bar

Accuracy
± 1 mm

Frequency
6 GHz
26 GHz
80 GHz

Beam angle
≥ 3°

Materials, wetted parts
PTFE
PVDF
316L
PP
PEEK

Threaded connection
≥ G $\frac{3}{4}$, ≥ $\frac{3}{4}$ NPT

Flange connection
≥ DN20, ≥ $\frac{3}{4}$ "

Hygienic fittings
Clamp ≥ 1 $\frac{1}{2}$ " - DIN32676, ISO2852
Slotted nut ≥ 2", DN50 - DIN 11851
Varivent ≥ DN25
hygienic fitting with tension flange DN32
hygienic fitting F40 with compression nut
Hygienic screw connections ≥ DN50 tube ø53 - DIN11864-1-A
Hygienic flange connection ≥ DN50 DIN11864-2
Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A
DRD connection ø 65 mm
SMS 1145 DN51

PRO

VEGASWING 63

[Show Product](#)



Process temperature
-50 ... 250 °C

Process pressure
-1 ... 64 bar

Version
Standard
Hygienic applications
with gas-tight leadthrough
with tube extension
with temperature adapter

Materials, wetted parts
PFA
316L
Alloy C22 (2.4602)
Alloy 400 (2.4360)
ECTFE
Enamel

Threaded connection
≥ G $\frac{3}{4}$, ≥ $\frac{3}{4}$ NPT

Flange connection
≥ DN25, ≥ 1"

Hygienic fittings
Clamp ≥ 1" - DIN32676, ISO2852
Slotted nut ≥ 1 $\frac{1}{2}$ ", ≥ DN40 - DIN 11851
Varivent ≥ DN25
hygienic fitting F40 with compression nut
SMS 1145 DN51
SMS DN38
Hygienic fittings ≥ DN25 - DIN11864-1-A
Hygienic flange connection DIN11864-2-A;
DN60(ISO)ø60,3
SMS socket piece DN38 PN6

Seal material
no media contact

Housing material
Plastic
Aluminium
Stainless steel (precision casting)
Stainless steel (electropolished)

Protection rating
IP66/IP67
IP66/IP68 (1 bar)
IP65