



Reliable

Certified materials according to FDA and EC 1935/2004 regulations

Cost effective

Minimal mounting depth ensures maintenance-free operation

User friendly

No adjustment required

Malt mill

Point level detection in the malt mill

The malt is prepared for mashing in the malt mill. Wet or dry malt mills are used depending on which brewing process is being used. During the milling process it is important to have a continuous flow of malt. If the mill is operated without malt, wear increases, which can lead to breakdowns and outages. To prevent the mill from running empty, the limit level is monitored.

[More details](#)



VEGAPOINT 24

Capacitive level switch for point level measurement at the inlet of the mill.

- Maintenance-free operation thanks to robust measuring system
- Reliable detection even under dusty conditions
- 360° display of the switching status

[Show Product](#)

VEGAPOINT 24[Show Product](#)**Measuring range - Distance**

-

Process temperature

-40 ... 115 °C

Process pressure

-1 ... 64 bar

Materials, wetted parts316L
PEEK**Threaded connection**

G½

Hygienic fittings

Clamp ≥ 2" - DN50 - DIN32676, ISO2852

Clamp ≥ 1" - DIN32676, ISO2852

Clamp ≥ 1½" - DIN32676, ISO2852

Protection rating

IP66/IP67

IP69

Output

Transistor (NPN/PNP)

IO-Link

Ambient temperature

-40 ... 70 °C