



### Reliable

Approved materials according to FDA and EC 1935/2004, as well as local certification

### Cost effective

Long service life guarantees uninterrupted operation

### User friendly


Uniform operation

## Drinking water pipeline

### Pressure monitoring and point level detection in the drinking water pipeline

To transport drinking water even to the remotest drinking water storage facilities, pumping stations generate the required water pressure, which is constantly monitored by a pressure transmitter. A level switch serves as dry run protection for the pumps.

[More details](#)



### VEGABAR 38

Pressure sensor for monitoring pressure in the drinking water pipeline

- CERTEC® measuring cell meets the hygiene requirements
- Long-term stability thanks to robust ceramic CERTEC® measuring cell
- Resistant to hydraulic pressure shocks

[Show Product](#)



### VEGAPOINT 21

Capacitive level switch as dry-run protection for drinking water pumps

- Wear and maintenance free for high plant availability
- Reliable switching function independent of process conditions
- Simple setup via Bluetooth operation

[Show Product](#)

## BASIC

## VEGABAR 38

[Show Product](#)**Measuring range - Pressure**

-1 ... 60 bar

**Process temperature**

-40 ... 130 °C

**Accuracy**

0.3 %

**Materials, wetted parts**

PVDF  
316L  
Duplex (1.4462)  
Ceramic

**Threaded connection**

≥ G½, ≥ ½ NPT

**Hygienic fittings**

Clamp ≥ 2", DN50 - DIN32676, ISO2852  
Clamp ≥ 1" - DIN32676, ISO2852  
Clamp ≥ ½" - DIN32676, ISO2852  
Slotted nut ≥ 1½", ≥ DN40 - DIN 11851  
Slotted nut ≥ DN25 - DIN 11851  
SMS DN38  
Hygienic fittings ≥ DN25 - DIN11864-1-A  
Hygienic fittings ≥ DN40 - DIN11864-1-A  
Varivent N50-40  
SMS DN25  
Ingold connection PN10  
Varivent F25

**Seal material**

EPDM  
FKM  
FFKM

**Housing material**

Plastic

**Protection rating**

IP66/IP67  
IP65

**Output**

4 ... 20 mA  
Three-wire (PNP/NPN, 4 ... 20 mA)  
IO-Link

## BASIC

## VEGAPOINT 21

[Show Product](#)**Measuring range - Distance**

-

**Process temperature**

-40 ... 115 °C

**Process pressure**

-1 ... 64 bar

**Materials, wetted parts**

316L  
PEEK

**Threaded connection**

≥ G½, ≥ ½ NPT

**Hygienic fittings**

Clamp ≥ 2", DN50 - DIN32676, ISO2852  
Clamp ≥ 1" - DIN32676, ISO2852  
Clamp ≥ ½" - DIN32676, ISO2852  
Slotted nut ≥ 1½", ≥ DN40 - DIN 11851  
Slotted nut ≥ DN25 - DIN 11851  
Slotted nut ≥ DN32 - DIN 11851

**Seal material**

EPDM  
FKM

**Protection rating**

IP66/IP67  
IP69

**Output**

Transistor (NPN/PNP)  
IO-Link

**Ambient temperature**

-40 ... 70 °C