



### Reliable

Approved materials according to FDA and EC 1935/2004, as well as local certification

### Cost effective

Long service life guarantees uninterrupted operation

### User friendly


Uniform operation

## Drinking water pipeline

### Pressure monitoring and point level detection in the drinking water pipeline

To transport drinking water even to the remotest drinking water storage facilities, pumping stations generate the required water pressure, which is constantly monitored by a pressure transmitter. A level switch serves as dry run protection for the pumps.

[More details](#)



### VEGABAR 38

Pressure sensor for monitoring pressure in the drinking water pipeline

- CERTEC® measuring cell meets the hygiene requirements
- Long-term stability thanks to robust ceramic CERTEC® measuring cell
- Resistant to hydraulic pressure shocks

[Show Product](#)



### VEGAPOINT 21

Capacitive level switch as dry-run protection for drinking water pumps

- Wear and maintenance free for high plant availability
- Reliable switching function independent of process conditions
- Simple setup via Bluetooth operation

[Show Product](#)

## BASIC

**VEGABAR 38**  
[Show Product](#)
**Measuring range - Pressure**

-1 ... 60 bar

**Process temperature**

-40 ... 130 °C

**Accuracy**

0.3 %

**Materials, wetted parts**

PVDF  
 316L  
 Duplex (1.4462)  
 Ceramic

**Threaded connection**

≥ G½, ≥ ½ NPT

**Hygienic fittings**

Clamp ≥ 2", DN50 - DIN32676, ISO2852  
 Clamp ≥ 1" - DIN32676, ISO2852  
 Clamp ≥ ½" - DIN32676, ISO2852  
 Slotted nut ≥ 1½", ≥ DN40 - DIN 11851  
 Slotted nut ≥ DN25 - DIN 11851  
 SMS DN38  
 Hygienic fittings ≥ DN25 - DIN11864-1-A  
 Hygienic fittings ≥ DN40 - DIN11864-1-A  
 Varivent N50-40  
 SMS DN25  
 Ingold connection PN10  
 Varivent F25

**Seal material**

EPDM  
 FKM  
 FFKM

**Housing material**

Plastic

**Protection rating**

IP66/IP67  
 IP65

**Output**

4 ... 20 mA  
 Three-wire (PNP/NPN, 4 ... 20 mA)  
 IO-Link

## BASIC

**VEGAPOINT 21**  
[Show Product](#)
**Measuring range - Distance**

-

**Process temperature**

-40 ... 115 °C

**Process pressure**

-1 ... 64 bar

**Materials, wetted parts**

316L  
 PEEK

**Threaded connection**

≥ G½, ≥ ½ NPT

**Hygienic fittings**

Clamp ≥ 2", DN50 - DIN32676, ISO2852  
 Clamp ≥ 1" - DIN32676, ISO2852  
 Clamp ≥ ½" - DIN32676, ISO2852  
 Slotted nut ≥ 1½", ≥ DN40 - DIN 11851  
 Slotted nut ≥ DN25 - DIN 11851  
 Slotted nut ≥ DN32 - DIN 11851

**Seal material**

EPDM  
 FKM

**Protection rating**

IP66/IP67  
 IP69

**Output**

Transistor (NPN/PNP)  
 IO-Link

**Ambient temperature**

-40 ... 70 °C