



Reliable

Redundant measurement for highest safety standards

Cost effective

Maintenance-free operation

User friendly


Easy installation

BTX separators

Level measurement and point level detection in the BTX separators

Precise interface monitoring in refinery separators is critical to product quality because it confirms there is complete separation. For liquid-liquid interface in a BTX (benzene, toluene, xylene) separator, an accurate measurement helps control the quality of the separator's output and thus helps to extend equipment life in downstream units by avoiding potentially expensive operating issues.

[More details](#)



VEGASWING 63

Vibrating level switch for overflow protection in BTX separators

- High level switch provides redundancy
- Maximum flexibility through switching point adaptable to the application
- Switching point is unaffected by media properties

[Show Product](#)



VEGAFLEX 81 and magnetic level indicator

Guided wave radar sensor and magnetic level indicator for monitoring of the separation layer

- Guided wave radar and magnetic level indicator provide redundancy
- Dual measurement capability provides both total level and interface level
- Continuous reporting increases operational efficiency

[Show Product](#)

PRO

VEGASWING 63[Show Product](#)**Process temperature**

-50 ... 250 °C

Process pressure

-1 ... 64 bar

Version

Standard
 Hygienic applications
 with gas-tight leadthrough
 with tube extension
 with temperature adapter

Materials, wetted parts

PFA
 316L
 Alloy C22 (2.4602)
 Alloy 400 (2.4360)
 ECTFE
 Enamel

Threaded connection

≥ G¾, ≥ ¾ NPT

Flange connection

≥ DN25, ≥ 1"

Hygienic fittings

Clamp ≥ 1" - DIN32676, ISO2852
 Slotted nut ≥ 1½", ≥ DN40 - DIN 11851
 Varivent ≥ DN25
 hygienic fitting F40 with compression nut
 SMS 1145 DN51
 SMS DN38
 Hygienic fittings ≥ DN25 - DIN11864-1-A
 Hygienic flange connection DIN11864-2-A;
 DN60(ISO)ø60,3
 SMS socket piece DN38 PN6

Seal material

no media contact

Housing material

Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)

Protection rating

IP66/IP67
 IP66/IP68 (1 bar)
 IP65

PRO

VEGAFLEX 81 and magnetic level indicator[Show Product](#)**Measuring range - Distance**

75 m

Process temperature

-60 ... 200 °C

Process pressure

-1 ... 40 bar

Accuracy

± 2 mm

Version

Basic version for exchangeable cable ø 2; ø 4 mm
 Basic version for exchangeable rod ø 8 mm
 Basic version for exchangeable rod ø 12 mm
 Coax version ø 21.3 mm for ammonia application
 Coax version ø 21.3 mm with single hole
 Coax version ø 21.3 mm with multiple hole
 Coax version ø 42.2 mm with multiple hole
 Exchangeable rod ø 8 mm
 Exchangeable rod ø 12 mm
 Exchangeable cable ø 2 mm with gravity weight
 Exchangeable cable ø 4 mm with gravity weight
 Exchangeable cable ø 2 mm with centering weight
 Exchangeable cable ø 4 mm with centering weight
 Exchangeable cable ø 4 mm without weight
 exchangeable, PFA-coated cable ø4 mm with non-coated
 centering weight

Materials, wetted parts

PFA
 316L
 Alloy C22 (2.4602)
 Alloy 400 (2.4360)
 Alloy C276 (2.4819)
 Duplex (1.4462)
 304L

Threaded connection

≥ G¾, ≥ ¾ NPT

Flange connection

≥ DN25, ≥ 1"

Seal material

EPDM
 FKM
 FFKM
 Silicone FEP coated
 Borosilicate glass

Housing material

Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)