



Reliable

High operational reliability through the use of chemically resistant materials

Cost effective

Yearly WHG test can be carried out by pressing a button

User friendly

Reliable, maintenance-free measurement

Storage tanks for acids

Level measurement and point level detection in storage tanks for acids

The raw water, which is usually extracted from a river, cannot be fed untreated directly into the turbine circuit of the plant. It has to be treated first. To neutralize the water, either sodium hydroxide (NaOH) or hydrochloric acid (HCl) is added. Level sensors supply the measurement data required to ensure a high availability of these chemicals and others used to treat the feed water.

[More details](#)



VEGAPULS 6X

The non-contact radar sensors are optimized for reliable measurement of aggressive media

- High acid resistance through optimized antenna design
- Reliable technology ensures high measurement certainty
- Very high operational reliability and long service life thanks to non-contact measuring method

[Show Product](#)



VEGASWING 63

The universally applicable vibrating level switch reliably prevents an overflowing of the container

- Product-independent switching point ensures millimetre-exact detection of the limit level
- Minimal costs for maintenance and servicing
- Available in different materials, includes Ex, WHG and SIL2 approvals

[Show Product](#)

PRO

VEGAPULS 6X

[Show Product](#)



Measuring range - Distance
120 m

Process temperature
-196 ... 450 °C

Process pressure
-1 ... 160 bar

Accuracy
± 1 mm

Frequency
6 GHz
26 GHz
80 GHz

Beam angle
≥ 3°

Materials, wetted parts
PTFE
PVDF
316L
PP
PEEK

Threaded connection
≥ G $\frac{3}{4}$, ≥ $\frac{3}{4}$ NPT

Flange connection
≥ DN20, ≥ $\frac{3}{4}$ "

Hygienic fittings
Clamp ≥ 1½" - DIN32676, ISO2852
Slotted nut ≥ 2", DN50 - DIN 11851
Varivent ≥ DN25
hygienic fitting with tension flange DN32
hygienic fitting F40 with compression nut
Hygienic screw connections ≥ DN50 tube ø53 - DIN11864-1-A
Hygienic flange connection ≥ DN50 DIN11864-2
Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-3-A
DRD connection ø 65 mm
SMS 1145 DN51

PRO

VEGASWING 63

[Show Product](#)



Process temperature
-50 ... 250 °C

Process pressure
-1 ... 64 bar

Version
Standard
Hygienic applications
with gas-tight leadthrough
with tube extension
with temperature adapter

Materials, wetted parts
PFA
316L
Alloy C22 (2.4602)
Alloy 400 (2.4360)
ECTFE
Enamel

Threaded connection
≥ G $\frac{3}{4}$, ≥ $\frac{3}{4}$ NPT

Flange connection
≥ DN25, ≥ 1"

Hygienic fittings
Clamp ≥ 1" - DIN32676, ISO2852
Slotted nut ≥ 1½", ≥ DN40 - DIN 11851
Varivent ≥ DN25
hygienic fitting F40 with compression nut
SMS 1145 DN51
SMS DN38
Hygienic fittings ≥ DN25 - DIN11864-1-A
Hygienic flange connection DIN11864-2-A;
DN60(ISO)ø60,3
SMS socket piece DN38 PN6

Seal material
no media contact

Housing material
Plastic
Aluminium
Stainless steel (precision casting)
Stainless steel (electropolished)

Protection rating
IP66/IP67
IP66/IP68 (1 bar)
IP65