



Reliable


Certain measurement even during filling

Cost effective

Reliable measurement of the total material volume in the silo

User friendly

Simple installation and setup



Lime silo

Level measurement and high level detection in the lime silo

In the nitrogen and phosphorus removal stage, lime is used to stabilize the pH value. Stored in silos, the lime is added to the wastewater as a solid or as an aqueous suspension. The silo content is measured by a radar sensor and a point level sensor detects the maximum level and transmits a full signal.

More details



VEGAPULS C 23

Non-contact level measurement with radar in the lime silo

- Maintenance-free operation thanks to non-contact measuring method
- Reliable measurement despite strong dust generation and buildup on the sensor
- Very good focusing allows exact measurement even with material deposits on the silo walls

[Show Product](#)



VEGACAP 65

Point level detection for full signal during filling

- Point level detection for reliable high level alarm during filling
- Mechanically robust sensor version guarantees long service life
- cable length shortened for easy adaptation to vessel size

[Show Product](#)



VEGATOR 141

Double channel signal conditioning instrument for level detection

- Simple adjustment of the switching point through a potentiometer
- Clearly visible switching status via LED
- Simple installation through carrier rail mounting as well as detachable, coded terminals

[Show Product](#)

BASIC

VEGAPULS C 23

[Show Product](#)**Measuring range - Distance**

30 m

Process temperature

-40 ... 80 °C

Process pressure

-1 ... 3 bar

Accuracy

± 2 mm

Frequency

80 GHz

Beam angle

4°

Materials, wetted parts

PVDF

Threaded connection

G1, 1 NPT, R1

Protection rating

IP66/IP68 (3 bar), Type 6P

Output4 ... 20 mA/HART
Modbus
SDI-12

PRO

VEGACAP 65

[Show Product](#)**Measuring range - Distance**

-

Process temperature

-50 ... 200 °C

Process pressure

-1 ... 64 bar

Version

Cable ø 6 mm with screening tube without weight
 Cable ø 6 mm with screening tube and gravity weight
 Cable ø 6 mm with gravity weight
 Cable ø 8 mm with abrasion protection without weight
 Cable ø 8 mm with abrasion protection and gravity weight
 Cable ø 8 mm with gravity weight
 PA cable ø 12 mm with screening tube and gravity weight

Materials, wetted parts

PTFE
 316L
 PA
 PEEK
 Steel

Threaded connection

≥ G1, ≥ 1 NPT

Flange connection

≥ DN50, ≥ 2"

Housing material

Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)

Protection rating

IP66/IP68 (0,2 bar)
 IP66/IP67
 IP66/IP68 (1 bar)

Output

Relay (DPDT)
 Contactless electronic switch
 Transistor (NPN/PNP)
 Two-wire

VEGATOR 141

[Show Product](#)**Protection rating**

IP20

Input

1 x 4 ... 20 mA sensor input

Output

1 x operating relay (SPDT)
 Optionally 1 x fail safe relay output (SPDT)

Ambient temperature

-20 ... 60 °C

Signal input (specify)

4 ... 20 mA

Signal output (specify)

Operating relay
 Fail safe relay