



Reliable

Approvals for hazardous areas

Cost effective

Process instrumentation secures ongoing plant operation

User friendly


Standardised operation of all sensors

Storage tanks for alcohol

Level measurement and point level detection in the storage tank

Alcohol storage tanks are considered potentially explosive and are therefore kept in special rooms. When the alcohol is needed, it is pumped directly to the appropriate production vessel through a "ring main" supply system. Reliable measuring instruments are required for dependable measurement of the level in the tank and for monitoring the feed pressure in the pipeline.

[More details](#)



VEGABAR 82

Pressure transmitter for level measurement in the alcohol tank and for monitoring pressure in the supply main

- External housing allows easy reading of measured values in hazardous areas
- Small process fittings on the pipeline
- Resistant to dynamic CIP and SIP cleaning

[Show Product](#)



VEGASWING 63

Vibrating level switch in the alcohol tank for overflow protection

- Maintenance-free tuning fork reliably detects switch-off point regardless of the consistency of the alcohols
- Simple setup without adjustment
- Maximum reliability and safety in hazardous areas

[Show Product](#)

PRO

VEGABAR 82
[Show Product](#)



Measuring range - Distance

-

Measuring range - Pressure

-1 ... 100 bar

Process temperature

-40 ... 150 °C

Process pressure

-1 ... 100 bar

Accuracy

0.05 %

Materials, wetted parts

PVDF
 316L
 Alloy C22 (2.4602)
 PP
 1.4057
 1.4410
 Alloy C276 (2.4819)
 Duplex (1.4462)
 Titanium Grade 2 (3.7035)

Threaded connection

≥ G½, ≥ ½ NPT

Flange connection

≥ DN15, ≥ ½"

Hygienic fittings

Clamp ≥ 1" - DIN32676, ISO2852
 Slotted nut ≥ DN25 - DIN 11851
 hygienic fitting with tension flange DN32
 hygienic fitting F40 with compression nut
 DRD connection ø 65 mm
 SMS 1145 DN51
 SMS DN38
 Swagelok VCR screwing
 Varivent G125
 Varivent N50-40
 for NEUMO BioControl D50 PN16 / 316L

Seal material

EPDM
 FKM
 FFKM

PRO

VEGASWING 63
[Show Product](#)



Process temperature

-50 ... 250 °C

Process pressure

-1 ... 64 bar

Version

Standard
 Hygienic applications
 with gas-tight leadthrough
 with tube extension
 with temperature adapter

Materials, wetted parts

PFA
 316L
 Alloy C22 (2.4602)
 Alloy 400 (2.4360)
 ECTFE
 Enamel

Threaded connection

≥ G¾, ≥ ¾ NPT

Flange connection

≥ DN25, ≥ 1"

Hygienic fittings

Clamp ≥ 1" - DIN32676, ISO2852
 Slotted nut ≥ 1½", ≥ DN40 - DIN 11851
 Varivent ≥ DN25
 hygienic fitting F40 with compression nut
 SMS 1145 DN51
 SMS DN38
 Hygienic fittings ≥ DN25 - DIN11864-1-A
 Hygienic flange connection DIN11864-2-A;
 DN60(ISO)ø60,3
 SMS socket piece DN38 PN6

Seal material

no media contact

Housing material

Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)

Protection rating

IP66/IP67
 IP66/IP68 (1 bar)
 IP65