



Reliable

Redundant measurement for highest safety standards

Cost effective

Maintenance-free operation

User friendly

Easy installation

Separator

Level and interface measurement and point level detection in separators

Exact interface measurement in separators is important for ensuring the quality of the separation process. Continuous control of the interface between oil and water ensures that oil is not inadvertently withdrawn instead of water. This saves costs and increases the efficiency of the plant. A vibrating level switch serves as an additional overflow protection mechanism.

[More details](#)



VEGASWING 63

Vibrating level switch for overflow protection in separators

- Additional security thanks to diverse redundancy
- Easy setup without medium saves time and money
- Increased plant availability, as function test can be performed during operation

[Show Product](#)



VEGAFLEX 81 and magnetic level indicator

Guided wave radar and magnetic level indicator for level and interface measurement

- Redundant measurement through the combination of guided radar sensor and magnetic level indicator
- Evaluation of two different measured values possible: level and interface
- Totally reliable measurement, even with emulsions

[Show Product](#)

PRO

VEGASWING 63[Show Product](#)**Process temperature**

-50 ... 250 °C

Process pressure

-1 ... 64 bar

Version

Standard
 Hygienic applications
 with gas-tight leadthrough
 with tube extension
 with temperature adapter

Materials, wetted parts

PFA
 316L
 Alloy C22 (2.4602)
 Alloy 400 (2.4360)
 ECTFE
 Enamel

Threaded connection≥ G $\frac{3}{4}$, ≥ $\frac{3}{4}$ NPT**Flange connection**

≥ DN25, ≥ 1"

Hygienic fittings

Clamp ≥ 1" - DIN32676, ISO2852
 Slotted nut ≥ 1½", ≥ DN40 - DIN 11851
 Varivent ≥ DN25
 hygienic fitting F40 with compression nut
 SMS 1145 DN51
 SMS DN38
 Hygienic fittings ≥ DN25 - DIN11864-1-A
 Hygienic flange connection DIN11864-2-A;
 DN60(ISO)ø60,3
 SMS socket piece DN38 PN6

Seal material

no media contact

Housing material

Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)

Protection rating

IP66/IP67
 IP66/IP68 (1 bar)
 IP65

PRO

VEGAFLEX 81 and magnetic level indicator[Show Product](#)**Measuring range - Distance**

75 m

Process temperature

-60 ... 200 °C

Process pressure

-1 ... 40 bar

Accuracy

± 2 mm

Version

Basic version for exchangeable cable ø 2; ø 4 mm
 Basic version for exchangeable rod ø 8 mm
 Basic version for exchangeable rod ø 12 mm
 Coax version ø 21.3 mm for ammonia application
 Coax version ø 21.3 mm with single hole
 Coax version ø 21.3 mm with multiple hole
 Coax version ø 42.2 mm with multiple hole
 Exchangeable rod ø 8 mm
 Exchangeable rod ø 12 mm
 Exchangeable cable ø 2 mm with gravity weight
 Exchangeable cable ø 4 mm with gravity weight
 Exchangeable cable ø 2 mm with centering weight
 Exchangeable cable ø 4 mm with centering weight
 Exchangeable cable ø 4 mm without weight
 exchangeable, PFA-coated cable ø4 mm with non-coated
 centering weight

Materials, wetted parts

PFA
 316L
 Alloy C22 (2.4602)
 Alloy 400 (2.4360)
 Alloy C276 (2.4819)
 Duplex (1.4462)
 304L

Threaded connection≥ G $\frac{3}{4}$, ≥ $\frac{3}{4}$ NPT**Flange connection**

≥ DN25, ≥ 1"

Seal material

EPDM
 FKM
 FFKM
 Silicone FEP coated
 Borosilicate glass

Housing material

Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)