



#### Reliable

Redundant measurement for highest safety standards

#### Cost effective

Maintenance-free operation

#### User friendly

Easy installation

## Separator

### Level and interface measurement and point level detection in separators

Exact interface measurement in separators is important for ensuring the quality of the separation process. Continuous control of the interface between oil and water ensures that oil is not inadvertently withdrawn instead of water. This saves costs and increases the efficiency of the plant. A vibrating level switch serves as an additional overflow protection mechanism.

[More details](#)



#### VEGASWING 63

Vibrating level switch for overflow protection in separators

- Additional security thanks to diverse redundancy
- Easy setup without medium saves time and money
- Increased plant availability, as function test can be performed during operation

[Show Product](#)



#### VEGAFLEX 81 and magnetic level indicator

Guided wave radar and magnetic level indicator for level and interface measurement

- Redundant measurement through the combination of guided radar sensor and magnetic level indicator
- Evaluation of two different measured values possible: level and interface
- Totally reliable measurement, even with emulsions

[Show Product](#)

PRO

**VEGASWING 63**[Show Product](#)**Process temperature**

-50 ... 250 °C

**Process pressure**

-1 ... 64 bar

**Version**

Standard  
 Hygienic applications  
 with gas-tight leadthrough  
 with tube extension  
 with temperature adapter

**Materials, wetted parts**

PFA  
 316L  
 Alloy C22 (2.4602)  
 Alloy 400 (2.4360)  
 ECTFE  
 Enamel

**Threaded connection**≥ G $\frac{3}{4}$ , ≥  $\frac{3}{4}$  NPT**Flange connection**

≥ DN25, ≥ 1"

**Hygienic fittings**

Clamp ≥ 1" - DIN32676, ISO2852  
 Slotted nut ≥ 1½", ≥ DN40 - DIN 11851  
 Varivent ≥ DN25  
 hygienic fitting F40 with compression nut  
 SMS 1145 DN51  
 SMS DN38  
 Hygienic fittings ≥ DN25 - DIN11864-1-A  
 Hygienic flange connection DIN11864-2-A;  
 DN60(ISO)ø60,3  
 SMS socket piece DN38 PN6

**Seal material**

no media contact

**Housing material**

Plastic  
 Aluminium  
 Stainless steel (precision casting)  
 Stainless steel (electropolished)

**Protection rating**

IP66/IP67  
 IP66/IP68 (1 bar)  
 IP65

PRO

**VEGAFLEX 81 and magnetic level indicator**[Show Product](#)**Measuring range - Distance**

75 m

**Process temperature**

-60 ... 200 °C

**Process pressure**

-1 ... 40 bar

**Accuracy**

± 2 mm

**Version**

Basic version for exchangeable cable ø 2; ø 4 mm  
 Basic version for exchangeable rod ø 8 mm  
 Basic version for exchangeable rod ø 12 mm  
 Coax version ø 21.3 mm for ammonia application  
 Coax version ø 21.3 mm with single hole  
 Coax version ø 21.3 mm with multiple hole  
 Coax version ø 42.2 mm with multiple hole  
 Exchangeable rod ø 8 mm  
 Exchangeable rod ø 12 mm  
 Exchangeable cable ø 2 mm with gravity weight  
 Exchangeable cable ø 4 mm with gravity weight  
 Exchangeable cable ø 2 mm with centering weight  
 Exchangeable cable ø 4 mm with centering weight  
 Exchangeable cable ø 4 mm without weight  
 exchangeable, PFA-coated cable ø4 mm with non-coated  
 centering weight

**Materials, wetted parts**

PFA  
 316L  
 Alloy C22 (2.4602)  
 Alloy 400 (2.4360)  
 Alloy C276 (2.4819)  
 Duplex (1.4462)  
 304L

**Threaded connection**≥ G $\frac{3}{4}$ , ≥  $\frac{3}{4}$  NPT**Flange connection**

≥ DN25, ≥ 1"

**Seal material**

EPDM  
 FKM  
 FFKM  
 Silicone FEP coated  
 Borosilicate glass

**Housing material**

Plastic  
 Aluminium  
 Stainless steel (precision casting)  
 Stainless steel (electropolished)