



Reliable

Reliable measurement under tough operating conditions

Cost effective

Optimal filling of silo vehicles

User friendly

Simple setup and commissioning

Truck loading

Point level detection during the loading of trucks

Dust-free, closed loading systems are needed for fine aggregates and finished products such as cement. Automated loading of trucks is preferred in the industry and, while the load quantity is determined with a weighing system, it must be ensured that the truck is in the correct place and not overfilled. Reliable point level detection and vehicle positioning shortens loading times, increases throughput and improves the efficiency of the entire system.

[More details](#)



VEGAWAVE 61

Overfill protection with vibrating level switch

- Reliable operation even in extremely dusty environment
- Independent of the properties of the bulk solid materials and the bulk density
- Long service life thanks to robust sensor design

[Show Product](#)



VEGAMIP 61

Position detection of vehicles with radar

- Reliable position detection in all weather conditions
- Fast and precise detection of a vehicle's position
- Maintenance-free operation thanks to non-contact measuring method

[Show Product](#)

PRO

PRO

VEGAWAVE 61
[Show Product](#)

Measuring range - Distance

-

Process temperature

-50 ... 250 °C

Process pressure

-1 ... 25 bar

Version

Standard
 Detection of solids in water
 with temperature adapter

Materials, wetted parts

316L

Threaded connection

≥ G1½, ≥ 1½ NPT

Flange connection

≥ DN50, ≥ 2"

Hygienic fittings

Clamp ≥ 2", DN50 - DIN32676, ISO2852

Seal material

no media contact

Housing material

Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)

VEGAMIP 61
[Show Product](#)

Measuring range - Distance

100 m

Process temperature

-40 ... 80 °C

Process pressure

-1 ... 4 bar

Version

hygienically encapsulated horn antenna
 for separate horn antenna
 with horn antenna ø 40 mm
 with horn antenna ø 48 mm
 with horn antenna ø 75 mm
 with horn antenna ø 95 mm
 with plastic horn antenna ø 80 mm
 Horn antenna ø 1½"
 with encapsulated horn antenna

Materials, wetted parts

PTFE
 316L
 1.4848
 PP

Threaded connection

G1½, 1½ NPT

Flange connection

≥ DN50, ≥ 2"

Hygienic fittings

Slotted nut ≥ 2", DN50 - DIN 11851
 Varivent ≥ DN25
 DRD connection ø 65 mm
 for NEUMO BioControl D50 PN16 / 316L

Seal material

FKM
 FFKM

Housing material

Plastic
 Aluminium
 Stainless steel (precision casting)
 Stainless steel (electropolished)