



Reliable

Reliable measuring results guarantee consistent quality

Cost effective

High system availability thanks to maintenance-free sensor

User friendly

Simple installation with clamping system and additional heat protection

Reactor with fruit concentrate

Density measurement in the pipeline

The reactor is filled with concentrated fruit juice and heated. In order to achieve a higher density, the water content is reduced through evaporation. As soon as the required Brix (density) value is reached, the syrupy fruit juice concentrate is pumped out. The concentrate is then pumped over to a filling machine to be stored in barrels or to a cooling machine where it is hardened and granulated. Reliable density measurement is used to monitor quality in the production process.

[More details](#)



MINITRAC 31

Radiometric sensor for density measurement in pipelines

- Reliable density measurement guarantees consistent product quality
- Exact measuring results independent of process conditions and media properties
- Compact sensor allows easy installation

[Show Product](#)

MINITRAC 31
[Show Product](#)**Measuring range - Distance**

-

Process temperature

-40 ... 60 °C

Process pressure

-

Accuracy

0.1 %

Materials, wetted parts

No wetted material

Seal material

no media contact

Housing materialAluminium
Stainless steel (precision casting)**Protection rating**

IP66/IP67

OutputProfibus PA
Foundation Fieldbus
Four-wire: 4 ... 20 mA/HART**Ambient temperature**

-40 ... 60 °C