



#### Reliable

Certified hygienic design (3A/EHEDG) and approved materials according to EC 1935/2004 and FDA

#### Cost effective

Certified hygienic design of the sensors reduces cleaning time

#### User friendly

Simple installation and setup

## Storage container for rennet

### Level measurement and point level detection in the storage container

The rennet is needed to coagulate the milk when making cheese. It is stored in a storage container and metered out into the cheese vat as needed. Reliable level and point level detection are essential to ensure that sufficient rennet is on hand for continuous cheese production.

[More details](#)



#### VEGABAR 83

Pressure transmitter for hydrostatic level measurement

- Reliable measurement at all temperatures through mechanical decoupling
- Good cleanability thanks to flush-mounted installation
- Robust measuring cell guarantees long-term stability

[Show Product](#)



#### VEGAPOINT 23

Capacitive level sensor as overflow protection

- Compact design facilitates cleaning
- Reliable detection of the medium, independent of buildup
- 360° display of the switching status

[Show Product](#)

PRO

BASIC

**VEGABAR 83**  
[Show Product](#)



**VEGAPOINT 23**  
[Show Product](#)



**Measuring range - Distance**

-

**Measuring range - Pressure**

-1 ... 1000 bar

**Process temperature**

-40 ... 200 °C

**Process pressure**

-1 ... 1000 bar

**Accuracy**

0.075 %

**Materials, wetted parts**

316L  
 Alloy C22 (2.4602)  
 316Ti (1.4571)  
 Alloy C4 (2.4610)

**Threaded connection**

≥ G½, ≥ ½ NPT

**Flange connection**

≥ DN25, ≥ 1"

**Hygienic fittings**

Slotted nut ≥ DN25 - DIN 11851  
 Varivent ≥ DN25  
 hygienic fitting with tension flange DN32  
 Hygienice flange connection ≥ DN50 DIN11864-2  
 SMS 1145 DN51  
 SMS DN38  
 Hygienic fittings ≥ DN33 - DIN11864-1-A  
 Hyg. collar clamp adapter DN40PN40 DIN11864-3-A  
 Hyg. clamp connection DIN11864-3-A; DN50 Rohr ø53  
 Swagelok VCR screwing  
 Varivent G125

**Seal material**

no media contact

**Measuring range - Distance**

-

**Process temperature**

-40 ... 115 °C

**Process pressure**

-1 ... 64 bar

**Materials, wetted parts**

316L  
 PEEK

**Threaded connection**

≥ G½, ≥ ½ NPT

**Hygienic fittings**

Clamp ≥ 2", DN50 - DIN32676, ISO2852  
 Clamp ≥ 1" - DIN32676, ISO2852  
 Clamp ≥ 1½" - DIN32676, ISO2852  
 Slotted nut ≥ 1½", ≥ DN40 - DIN 11851  
 Slotted nut ≥ DN25 - DIN 11851  
 Slotted nut ≥ DN32 - DIN 11851

**Seal material**

EPDM  
 FKM

**Protection rating**

IP66/IP67  
 IP69

**Output**

Transistor (NPN/PNP)  
 IO-Link

**Ambient temperature**

-40 ... 70 °C