



#### Reliable

Reliable measurement unaffected by medium

#### Cost effective

Continuous operation of the power equipment is assured

#### User friendly


Simple installation

## Hydraulic oil reservoir tank

### Level measurement in the reservoir tank for hydraulic oil

The hydraulic oil used to transmit power circulates in a closed system. However, it is gradually lost due to lubrication points and leakages in the power equipment. To ensure optimum operation of the power equipment, the level in every hydraulic oil reservoir tank must be monitored for replenishment.

[More details](#)



### VEGAFLEX 81

Level measurement with guided radar in the hydraulic oil reservoir tank

- Precise measurement, independent of media properties
- High measurement reliability even with buildup
- Simple setup and commissioning saves time

[Show Product](#)

**VEGAFLEX 81**[Show Product](#)**Measuring range - Distance**

75 m

**Process temperature**

-60 ... 200 °C

**Process pressure**

-1 ... 40 bar

**Accuracy**

± 2 mm

**Version**

Basic version for exchangeable cable  $\varnothing$  2;  $\varnothing$  4 mm  
 Basic version for exchangeable rod  $\varnothing$  8 mm  
 Basic version for exchangeable rod  $\varnothing$  12 mm  
 Coax version  $\varnothing$  21.3 mm for ammonia application  
 Coax version  $\varnothing$  21.3 mm with single hole  
 Coax version  $\varnothing$  21.3 mm with multiple hole  
 Coax version  $\varnothing$  42.2 mm with multiple hole  
 Exchangeable rod  $\varnothing$  8 mm  
 Exchangeable rod  $\varnothing$  12 mm  
 Exchangeable cable  $\varnothing$  2 mm with gravity weight  
 Exchangeable cable  $\varnothing$  4 mm with gravity weight  
 Exchangeable cable  $\varnothing$  2 mm with centering weight  
 Exchangeable cable  $\varnothing$  4 mm with centering weight  
 Exchangeable cable  $\varnothing$  4 mm without weight  
 exchangeable, PFA-coated cable  $\varnothing$  4 mm with non-coated centering weight

**Materials, wetted parts**

PFA  
 316L  
 Alloy C22 (2.4602)  
 Alloy 400 (2.4360)  
 Alloy C276 (2.4819)  
 Duplex (1.4462)  
 304L

**Threaded connection** $\geq G\frac{3}{4}$ ,  $\geq \frac{3}{4}$  NPT**Flange connection** $\geq DN25$ ,  $\geq 1"$ **Seal material**

EPDM  
 FKM  
 FFKM  
 Silicone FEP coated  
 Borosilicate glass

**Housing material**

Plastic  
 Aluminium  
 Stainless steel (precision casting)  
 Stainless steel (electropolished)