



Reliable

Reliable measurement even with oxygen and hydrogen gasses

Cost effective

Precise measuring results for efficient regulation of the process

User friendly


Direct installation in small tanks with internal structures

PEM electrolyser

Level and pressure measurement in the PEM electrolyser

In the electrolyser, renewable energy is used to split water (H₂O) into its individual components hydrogen (H) and oxygen (O). Green hydrogen is thus produced in a CO₂-free cycle. The PEM electrolyser, uses a proton exchange membrane that is continuously flushed with ultrapure water. An electrical potential causes protons to migrate through the membrane. Hydrogen is produced on the cathode side and oxygen on the anode side. On the oxygen side, level measurement is used to regulate the ultrapure water. On the hydrogen side, it monitors the excess water. The pressure sensors monitor the pressure in the feed line on the oxygen side and in the discharge line on the hydrogen side.

[More details](#)



VEGABAR 28

Pressure measurement in the inlet and outlet of the PEM electrolyser

- Reliable measurement of hydrogen and oxygen
- Simple setup and commissioning via Bluetooth
- Resistance to internal ignition in oxygen applications available as per 'BAM assessment'

[Show Product](#)



VEGAPULS 6X

Level measurement with radar for regulation of water quantities

- Reliable measurement thanks to non-contact measuring principle
- High plant availability, because sensor is wear and maintenance free
- Sensor version for high-purity oxygen applications (EIGA 33/18 and ASTM G93) also available

[Show Product](#)

BASIC

PRO

VEGABAR 28
[Show Product](#)
**Measuring range - Pressure**

-1 ... 60 bar

Process temperature

-40 ... 130 °C

Accuracy

0.3 %

Materials, wetted parts

PVDF
 Duplex (1.4462)
 Ceramic
 316/316L

Threaded connection

≥ G½, ≥ ½ NPT

Hygienic fittings

Clamp ≥ 2", DN50 - DIN32676, ISO2852
 Clamp ≥ 1" - DIN32676, ISO2852
 Clamp ≥ 1½" - DIN32676, ISO2852
 Slotted nut ≥ DN25 - DIN 11851
 Slotted nut ≥ DN32 - DIN 11851
 SMS 1145 DN51
 SMS DN38
 Hygienic fittings ≥ DN25 - DIN11864-1-A
 Hygienic fittings ≥ DN40 - DIN11864-1-A
 Varivent N50-40
 SMS DN25
 Ingold connection PN10
 Varivent F25

Seal material

EPDM
 FKM
 FFKM

Protection rating

IP65
 IP68 (0,5 bar)/IP69

Output

4 ... 20 mA
 Three-wire (PNP/NPN, 4 ... 20 mA)
 IO-Link

Ambient temperature

-40 ... 70 °C

VEGAPULS 6X
[Show Product](#)
**Measuring range - Distance**

120 m

Process temperature

-196 ... 450 °C

Process pressure

-1 ... 160 bar

Accuracy

± 1 mm

Frequency

6 GHz
 26 GHz
 80 GHz

Beam angle

≥ 3°

Materials, wetted parts

PTFE
 PVDF
 316L
 PP
 PEEK

Threaded connection

≥ G¾, ≥ ¾ NPT

Flange connection

≥ DN20, ≥ ¾"

Hygienic fittings

Clamp ≥ 1½" - DIN32676, ISO2852
 Slotted nut ≥ 2", DN50 - DIN 11851
 Varivent ≥ DN25
 hygienic fitting with tension flange DN32
 hygienic fitting F40 with compression nut
 Hygienic screw connections ≥ DN50 tube ø53 -
 DIN11864-1-A
 Hygienic flange connection ≥ DN50 DIN11864-2
 Hygienic clamp connection ≥ DN50 pipe Ø53 - DIN11864-
 3-A
 DRD connection ø 65 mm
 SMS 1145 DN51