

Reliable


Approved materials according to FDA and EC 1935/2004, as well as local certification

Cost effective

Efficient cleaning of the filter is possible even during continuous operation

User friendly

Maintenance-friendly thanks to front-flush mounting



Osmosis filter

Differential pressure measurement in an osmosis filter

Sea water is pressed through a semi-permeable membrane under high pressure. The semi-permeable membrane allows only water molecules to seep through. Salts, bacteria and viruses are retained in the filter. The finished product is almost the same as distilled water. A differential pressure measurement is needed to monitor the level of contamination across the filter.

More details



VEGADIF 85

Differential pressure transmitter for measuring the level of contamination in the filter

- · Highly accurate measurement of the smallest differential pressure
- · High reliability with integrated overload diaphragm system
- Static pressure output also possible through integrated sensor for multi parameter measurement

Show Product

VEGADIS 81

External display and adjustment unit for 4 ... 20 mA HART sensors

- Simple voltage supply of display via the existing 4 ... 20 mA current loop
- Easy-to-read display in plain text with additional graphical support menu
- Simple operation via four buttons and a clearly structured menu

Show Product

Mounting bracket for VEGADIF

Mounting bracket for differential pressure transmitter

- · Weatherproof and robust 304 stainless steel construction
- Simple wall or pipe mounting

Show Product



PRO

PRO		
VEGADIF 85 Show Product		
	T	
Measuring ran -40 40 bar	nge - Pressure	
Process temp -40 105 °C	erature	
Process pressure -1 400 bar		
Accuracy 0.065 %		
Materials, wet 316L Tantalum Alloy C276 (2.4 Monel	-	
Threaded con 1⁄4 - 18 NPT	nection	
Flange conne ≥ DN32, ≥ 1%"	ction	
Seal material EPDM FKM Copper		
	rial (precision casting) (electropolished)	
Protection rat IP66/IP68 (0,2 IP66/IP67 IP66/IP68 (1 ba	bar)	

VEGADIS 81 Show Product

Mounting bracket for VEGADIF Show Product





Housing material

Plastic

Aluminium Stainless steel (precision casting)

Protection rating

IP66/IP67

Ambient temperature

-20 ... 70 °C

Signal input (specify)

plics sensor (serial)

Signal output (specify)

Display

