



Reliable

Certified materials according to FDA and EC 1935/2004 regulations

Cost effective

Process instrumentation ensures continuous operation

User friendly

Simple setup and commissioning

Storage tank for liquid foodstuffs

Level measurement in storage tanks for liquid foodstuffs

In the food industry, liquid media such as glucose, fruit juice or syrup must always be kept in stock. To get them ready for the production process, some liquids must be either pre-cooled or pre-heated, while still in the storage tanks. This is done by means of a water-filled 'jacketed' container wall that can be either cooled or heated. To ensure uninterrupted production, a reliable level measurement is essential.

[More details](#)



VEGABAR 82

Pressure transmitter for level measurement in storage tanks with liquid media

- Hygienic design with certified process fittings
- High system availability: low maintenance thanks to self-monitoring, wear-free CERTEC® measuring cell
- Reaction time only 80 ms: rapid level changes are easily detected

[Show Product](#)

VEGABAR 82[Show Product](#)**Measuring range - Distance**

-

Measuring range - Pressure

-1 ... 100 bar

Process temperature

-40 ... 150 °C

Process pressure

-1 ... 100 bar

Accuracy

0.05 %

Materials, wetted parts

PVDF
 316L
 Alloy C22 (2.4602)
 PP
 1.4057
 1.4410
 Alloy C276 (2.4819)
 Duplex (1.4462)
 Titanium Grade 2 (3.7035)

Threaded connection

≥ G½, ≥ ½ NPT

Flange connection

≥ DN15, ≥ ½"

Hygienic fittings

Clamp ≥ 1" - DIN32676, ISO2852
 Slotted nut ≥ DN25 - DIN 11851
 hygienic fitting with tension flange DN32
 hygienic fitting F40 with compression nut
 DRD connection ø 65 mm
 SMS 1145 DN51
 SMS DN38
 Swagelok VCR screwing
 Varivent G125
 Varivent N50-40
 for NEUMO BioControl D50 PN16 / 316L

Seal material

EPDM
 FKM
 FFKM